

# DIN EN 14236:2018-12 (E)

## Ultrasonic domestic gas meters

---

<b>Contents</b>		<b>Page</b>
European foreword .....		5
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>8</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>8</b>
<b>3.2</b>	<b>Symbols .....</b>	<b>11</b>
<b>4</b>	<b>Normal operating conditions .....</b>	<b>13</b>
<b>4.1</b>	<b>Flow range .....</b>	<b>13</b>
<b>4.2</b>	<b>Maximum working pressure .....</b>	<b>13</b>
<b>4.3</b>	<b>Temperature range .....</b>	<b>13</b>
<b>4.4</b>	<b>Range of gases .....</b>	<b>14</b>
<b>4.5</b>	<b>Orientation .....</b>	<b>14</b>
<b>5</b>	<b>Metrological performance .....</b>	<b>14</b>
<b>5.1</b>	<b>General .....</b>	<b>14</b>
<b>5.2</b>	<b>Mode comparison .....</b>	<b>15</b>
<b>5.3</b>	<b>Permissible errors .....</b>	<b>15</b>
<b>5.4</b>	<b>Gas -- air relationship .....</b>	<b>16</b>
<b>5.5</b>	<b>Pressure absorption .....</b>	<b>17</b>
<b>5.6</b>	<b>Metrological stability .....</b>	<b>18</b>
<b>5.7</b>	<b>Immunity to contaminants in gas stream .....</b>	<b>18</b>
<b>5.8</b>	<b>Installation effects .....</b>	<b>20</b>
<b>5.9</b>	<b>Zero flow .....</b>	<b>20</b>
<b>5.10</b>	<b>Reverse flow .....</b>	<b>20</b>
<b>5.11</b>	<b>Low flow registration .....</b>	<b>21</b>
<b>5.12</b>	<b>High flow registration .....</b>	<b>21</b>
<b>5.13</b>	<b>Pulsed (unsteady) flow .....</b>	<b>21</b>
<b>5.14</b>	<b>Temperature sensitivity .....</b>	<b>22</b>
<b>6</b>	<b>Construction and materials .....</b>	<b>23</b>
<b>6.1</b>	<b>General .....</b>	<b>23</b>
<b>6.2</b>	<b>Robustness of meter case .....</b>	<b>23</b>
<b>6.3</b>	<b>Corrosion protection .....</b>	<b>32</b>
<b>6.4</b>	<b>Casework decorative finish .....</b>	<b>38</b>
<b>6.5</b>	<b>Ageing of non-metallic casework .....</b>	<b>38</b>
<b>6.6</b>	<b>Ageing of external surfaces of the meter, including index windows and adhesion of the index window .....</b>	<b>39</b>
<b>6.7</b>	<b>Protection against solar radiation .....</b>	<b>39</b>
<b>6.8</b>	<b>Resistance to external humidity .....</b>	<b>40</b>
<b>6.9</b>	<b>Flame retardance of external surfaces .....</b>	<b>41</b>
<b>6.10</b>	<b>Resistance to storage temperature range .....</b>	<b>41</b>
<b>6.11</b>	<b>Resistance to the effects of toluene/iso-octane vapour .....</b>	<b>41</b>
<b>6.12</b>	<b>Resistance to water vapour .....</b>	<b>44</b>
<b>6.13</b>	<b>Ageing .....</b>	<b>45</b>
<b>7</b>	<b>Optional features .....</b>	<b>46</b>
<b>7.1</b>	<b>Pressure measuring point .....</b>	<b>46</b>



<b>B.3</b>	<b>Certificates of conformity .....</b>	<b>67</b>
	<b>Annex C (normative) Meters with gas temperature conversion devices .....</b>	<b>69</b>
<b>C.1</b>	<b>Scope .....</b>	<b>69</b>
<b>C.2</b>	<b>Metrological performance .....</b>	<b>69</b>
	<b>Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2014/32/EU Measuring Instruments Directive aimed to be covered .....</b>	<b>73</b>
	<b>Bibliography .....</b>	<b>79</b>