

# DIN 3535-5:2020-07 (E)

## Seals for gas supply — Part 5: Sealing materials of rubber, cork and synthetic fibres for gas fittings and gas appliances

---

| <b>Contents</b> |   | <b>Page</b> |
|-----------------|---|-------------|
| Foreword .....  |   | 3           |
| <b>1</b>        | <b>Scope .....</b>  | <b>4</b>    |
| <b>2</b>        | <b>Normative references .....</b>                             | <b>4</b>    |
| <b>3</b>        | <b>Terms and definitions .....</b>                            | <b>5</b>    |
| <b>4</b>        | <b>Materials .....</b>  | <b>5</b>    |
| <b>4.1</b>      | <b>General .....</b>  | <b>5</b>    |
| <b>4.2</b>      | <b>Designation .....</b>                                      | <b>6</b>    |
| <b>5</b>        | <b>Requirements .....</b>                                     | <b>6</b>    |
| <b>5.1</b>      | <b>Properties as delivered .....</b>                          | <b>6</b>    |
| <b>5.2</b>      | <b>Properties after ageing .....</b>                          | <b>6</b>    |
| <b>5.3</b>      | <b>Properties after immersion and drying .....</b>            | <b>7</b>    |
| <b>6</b>        | <b>Testing .....</b>  | <b>7</b>    |
| <b>6.1</b>      | <b>Test samples and test documents .....</b>                  | <b>7</b>    |
| <b>6.1.1</b>    | <b>Test samples .....</b>                                     | <b>7</b>    |
| <b>6.1.2</b>    | <b>Test documents .....</b>                                   | <b>7</b>    |
| <b>6.2</b>      | <b>Scope of testing .....</b>                                 | <b>7</b>    |
| <b>6.2.1</b>    | <b>Testing of thickness .....</b>                             | <b>7</b>    |
| <b>6.2.2</b>    | <b>Testing properties as delivered .....</b>                  | <b>7</b>    |
| <b>6.2.3</b>    | <b>Testing properties after ageing .....</b>                  | <b>11</b>   |
| <b>6.2.4</b>    | <b>Testing of properties after immersion and drying .....</b> | <b>11</b>   |
| <b>6.3</b>      | <b>Test report .....</b>                                      | <b>12</b>   |