

DIN EN 12864:2006-03 (E)

Low-pressure, non adjustable regulators having a maximum outlet pressure of less than or equal to 200 mbar, with a capacity of less than or equal to 4 kg/h, and their associated safety devices for butane, propane or their mixtures

Contents		Page
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
3.1	General definitions	7
3.2	Definitions concerning gas	8
3.3	Definitions concerning pressures	8
3.4	Definitions concerning rates	9
4	Terminology	9
5	Structural characteristics	10
5.1	General	10
5.2	Materials	11
5.3	Special requirements	12
5.4	Mechanical strength	14
5.5	Soundness	15
5.6	Mechanical endurance	16
5.7	Resistance to humidity changes	16
5.8	Resistance to corrosion	16
6	Performance characteristics	17
7	Test methods	19
7.1	General conditions	19
7.2	Verification of structural characteristics	20
7.3	Verification of performance characteristics	28
8	Marking - Packaging - Instructions	32
8.1	General	32
8.2	Marking of the regulator	32
8.3	Packaging	33
8.4	Instructions for use and maintenance	33
Annex A (normative) Special requirements for regulators fitted with pressure or rate operated safety devices		34
A.1	Regulators fitted with an overpressure relief valve of a limited flow rate	34
A.2	Regulators fitted with an overpressure shut off device	35
A.3	Regulators fitted with an underpressure shut off safety device	37
A.4	Regulators fitted with an excess flow valve	38
Annex B (normative) Special requirements for regulators fitted with a temperature operated safety device		41
B.1	Definition	41
B.2	Structural characteristics	41
B.3	Performance characteristics	41

B.4	Test methods	41
Annex C (normative)	Special requirements for low pressure regulators under extreme temperature conditions	43
Annex D (normative)	Multimode connection regulator for LPG cylinders to supply appliances installed in caravans and motor caravans or freshwater boats	44
D.1	Scope	44
D.2	Design characteristics	44
D.3	Structural characteristics	45
D.4	Operating characteristics	47
D.5	Marking - Packaging - Instructions	48
Annex E (normative)	Complementary test requirements for non metallic thermoplastic or thermosetting materials used in the construction of regulators	52
E.1	Scope	52
E.2	Materials	52
E.3	Special conditions for carrying out the tests mentioned in the body of the standard	52
E.4	Special requirements	53
E.5	Sampling and order of tests	54
Annex F (normative)	Supplementary requirements for reinforced diaphragms and elastomeric seals used in LPG appliances and their associated equipment	55
Annex G (normative)	Inlet connections	56
Annex H (normative)	Outlet connections	89
Annex I (normative)	Special requirements for low pressure non adjustable regulators fitted with two or three outlets for outdoor use	104
I.1	Structural characteristics	104
I.2	Performance characteristics	104
I.3	Test methods	104
I.4	Marking	106
Annex J (normative)	Method for measuring leaks at test pressures less than or equal to 20 bar	107
J.1	Scope	107
J.2	Diagram of the test bench	107
J.3	Determination of coefficient K	108
J.4	Measurement of the leak	108
J.5	Checks	109
Annex K (normative)	Special requirements for regulators fitted with an inlet valve	110
K.1	Definition	110
K.2	Structural characteristics	110
K.3	Performance characteristics : mechanical strength	110
K.4	Test method	110
Annex L (informative)	Alternative test method for resistance to corrosion	111
L.1	Principle	111
L.2	Reagents	111
L.3	Apparatus	112
L.4	Test method	114
L.5	Results	114
Annex M (normative)	Regulator for LPG cylinders to supply appliances installed in seawater boats	117

M.1	Scope	117
M.2	General	117
M.3	Maximum guaranteed rate	117
M.4	Regulators fitted with a pressure relief valve	117
M.5	Vent	117
M.6	Connections	117
M.7	Material	117
M.8	Corrosion	118
M.9	Marking	118
M.10	Instructions for use and maintenance	118
Annex ZA (informative) Clauses of this European Standard addressing essential requirements or other provisions of EU directives		119