

# ISO 17268:2006-04 (E)

## Compressed hydrogen surface vehicle refuelling connection devices

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>General construction requirements .....</b>	<b>3</b>
<b>5</b>	<b>Nozzles .....</b>	<b>3</b>
<b>6</b>	<b>Standard receptacle dimensions .....</b>	<b>4</b>
<b>7</b>	<b>Receptacles .....</b>	<b>6</b>
<b>8</b>	<b>Instructions .....</b>	<b>6</b>
<b>9</b>	<b>Marking .....</b>	<b>6</b>
<b>10</b>	<b>Design verification test procedures .....</b>	<b>7</b>
<b>10.1</b>	<b>General requirements .....</b>	<b>7</b>
<b>10.2</b>	<b>User - Machine interface .....</b>	<b>7</b>
<b>10.3</b>	<b>Dropping .....</b>	<b>8</b>
<b>10.4</b>	<b>Leakage at room temperature .....</b>	<b>8</b>
<b>10.5</b>	<b>Valve operating handle .....</b>	<b>9</b>
<b>10.6</b>	<b>Receptacle vibration resistance .....</b>	<b>9</b>
<b>10.7</b>	<b>Abnormal loads .....</b>	<b>9</b>
<b>10.8</b>	<b>Rocking/twisting .....</b>	<b>10</b>
<b>10.9</b>	<b>Mounting hardware torque .....</b>	<b>11</b>
<b>10.10</b>	<b>Low and high temperatures .....</b>	<b>11</b>
<b>10.11</b>	<b>Durability and maintainability .....</b>	<b>12</b>
<b>10.12</b>	<b>Hydrostatic strength .....</b>	<b>15</b>
<b>10.13</b>	<b>Materials .....</b>	<b>15</b>
<b>10.14</b>	<b>Corrosion resistance .....</b>	<b>15</b>
<b>10.15</b>	<b>Deformation .....</b>	<b>16</b>
<b>10.16</b>	<b>Contamination test .....</b>	<b>16</b>
<b>10.17</b>	<b>Thermal cycle test .....</b>	<b>16</b>
<b>Annex A (informative)</b>	<b>Nozzle characteristics .....</b>	<b>19</b>