

# DIN EN 656/A1 :2006-12 (E)

Gas-fired central heating boilers\_ - Type\_B boilers of nominal heat input exceeding 70\_kW, but not exceeding 300\_kW

---

<b>Contents</b>		<b>Page</b>
	<b>Foreword</b>	<b>3</b>
<b>4</b>	<b>Classification of boilers</b>	<b>4</b>
<b>4.3</b>	<b>Type of technologies</b>	<b>4</b>
<b>5.3.1</b>	<b>General</b>	<b>5</b>
<b>5.4.1</b>	<b>General</b>	<b>5</b>
<b>5.8.5</b>	<b>Removal of condensate for low temperature boilers</b>	<b>5</b>
<b>5.16</b>	<b>Chemical composition of the condensate for low-temperature boilers</b>	<b>6</b>
<b>6.5.9</b>	<b>Condensate discharge blockage</b>	<b>6</b>
<b>6.7.1</b>	<b>Useful efficiency at the nominal heat input</b>	<b>6</b>
<b>6.7.2</b>	<b>Useful efficiency at part load</b>	<b>7</b>
<b>6.8</b>	<b>Non-condensation in the flue</b>	<b>7</b>
<b>6.9.1</b>	<b>General</b>	<b>7</b>
<b>6.12</b>	<b>Condensation in a standard boiler</b>	<b>7</b>
<b>7.1.1.3</b>	<b>Characteristics and choice of test gases</b>	<b>8</b>
<b>7.5.9</b>	<b>Condensate discharge blockage</b>	<b>8</b>
<b>7.6</b>	<b>Combustion</b>	<b>8</b>
<b>7.7.1</b>	<b>Useful efficiency at the nominal heat input</b>	<b>8</b>
<b>7.7.2.1</b>	<b>General</b>	<b>8</b>
<b>7.7.2.2</b>	<b>Direct method</b>	<b>9</b>
<b>7.7.2.2.1</b>	<b>General</b>	<b>9</b>
<b>7.7.2.2.2</b>	<b>Operating mode No. 1</b>	<b>9</b>
<b>7.7.2.2.3</b>	<b>Operating mode No. 2</b>	<b>9</b>
<b>7.7.2.3</b>	<b>Indirect method</b>	<b>9</b>
<b>7.7.2.3</b>	<b>Indirect method</b>	<b>10</b>
<b>7.7.2.3.1</b>	<b>Measurements</b>	<b>10</b>
<b>7.7.2.3.1.1</b>	<b>Useful efficiency at the nominal heat input at reduced water temperature</b>	<b>10</b>
<b>7.7.2.3.1.2</b>	<b>Efficiency at the minimum controlled rate</b>	<b>12</b>
<b>7.7.2.3.1.3</b>	<b>Standby loss</b>	<b>12</b>
<b>7.7.2.3.1.4</b>	<b>Pilot recovery factor</b>	<b>13</b>
<b>7.7.2.3.2</b>	<b>Calculation</b>	<b>13</b>
<b>7.8</b>	<b>Non-condensation in the flue</b>	<b>14</b>
<b>7.8</b>	<b>Criteria for condensation in the flue</b>	<b>14</b>
<b>7.8.1</b>	<b>Determination of the flue losses</b>	<b>14</b>
<b>7.8.2</b>	<b>Minimum temperature of the combustion products</b>	<b>14</b>
<b>7.12</b>	<b>Condensation in a standard boiler</b>	<b>14</b>
<b>8.1.3</b>	<b>Supplementary marking</b>	<b>14</b>
<b>8.2.1</b>	<b>Technical instructions for the installer</b>	<b>15</b>
	<b>Annex ZA (informative)</b>	<b>15</b>