DIN EN 1775:2007-10 (E)

Gas supply - Gas pipework for buildings - Maximum operating pressure less than or equal to 5 bar - Functional recommendations

Contents

Page

Foreword 4

1 Scope 6

2 Normative references 7

3 Terms and definitions 7
3.1 Definitions relating to pressures 7
3.2 Definitions relating to the gas installation 8
3.3 Definitions relating to means of isolation 9
3.4 Definitions relating to jointing methods 9
3.5 Definitions relating to fittings 10
3.6 Definitions relating to tests 11
3.7 Definitions relating to commissioning, operation and maintenance 11
3.8 Definitions relating to assembling processes 12
3.8.1 Definitions for welding 12
3.8.2 Definitions for soldering and brazing 12

4 Design 12
4.1 General 12
4.2 Selection of components 13
4.3 Location 13
4.4 Protection in case of fire 14
4.5 Sizing 14
4.6 Safety devices 15

5 Construction 16
5.1 Installation 16
5.2 Pipework jointing methods 16
5.2.1 Threaded joints 16
5.2.2 Welded, brazed, soldered and fusion joints 17
5.2.3 Mechanical joints 17
5.2.4 Pressed joints 17
5.2.5 Stainless steel pliable corrugated tubing system jointing 18
5.3 Entries through walls and floors 18
5.4 Corrosion 18
5.5 Means of isolation 18
5.6 Regulators and meters 19
5.7 Flexible appliance connectors 19

6 Testing 20
6.1 General recommendations 20
6.2 Recommendations relating to the safety of persons and property during testing 20
6.3 Test fluids 20
6.3.1 Fluids used 20
6.3.2 Use of inert gas 21
6.3.3 Utilisation of the gas to be distributed 21
6.4 Test conditions 21
6.5 Strength testing 21
6.6 Tightness testing 21
6.7 Additional tests 22

7 Commissioning 22
7.1 General 22
7.2 Admission of gas 23

8 Operation and maintenance 23
8.1 General 23
8.2 Maintenance 24
8.3 Abnormal situations 24
8.4 Leak detection 25
8.5 Work on operating pipework 25
8.6 Purging from gas 25

Annex A (informative) Resistance to high temperatures 27

A.1 General 27
A.2 Procedure A 27
A.2.1 Test criteria 27
A.2.2 Test method 27
A.3 Procedure B 28
A.3.1 Test criteria 28
A.3.2 Test method 29

Annex B (informative) General guidelines for the construction of joints 30

B.1 General 30
B.2 Installation operatives 30
B.3 Quality Control 31
B.4 Documentation 31

Annex C (informative) Guidelines for the construction of welded, brazed, soldered joints, and polyethylene fusion joints 32

C.1 Welding of steel 32
C.1.1 Materials 32
C.1.2 Approval of the welding procedure 32
C.1.3 Pipework with a maximum operating pressure (MOP) up to and including 0,1 bar and a wall thickness less than 4mm 32
C.1.4 Pipework with a maximum operating pressure (MOP) over 0,1 bar or wall thickness including and above 4 mm 33
C.2 Brazing and soldering of copper and copper alloys 34
C.2.1 Materials 34
C.2.2 Brazing and soldering procedure 34
C.2.3 Pipework with a maximum operating pressure (MOP) up to and including 0,1 bar 34
C.2.4 Pipework with a maximum operating pressure (MOP) over 0,1 bar 35
C.3 Fusion jointing of polyethylene 35
C.3.1 Materials 35
C.3.2 Polyethylene fusion jointing procedure 36
C.3.3 Qualification of personnel 36
C.3.4 Quality control 36

Annex D (informative) Guidelines for the construction of pressed joints 39

D.1 Jointing procedure with press fittings on copper pipes 39
D.1.1 General 39
D.1.2 Installation process 39
D.2 Jointing procedure with press fittings on multi-layer and PEX 40
D.2.1 General 40
D.2.2 Installation process 40

Annex E (informative) Guidelines for the construction of stainless steel pliable corrugated tubing systems 41

E.1 General 41
E.2 Components of the system 41
E.3 Stainless steel pliable corrugated tubing systems jointing procedure 41
E.3.1 General 41
E.3.2 Training of personnel 41
E.3.3 Quality control 42

Bibliography 43