

ISO 16840-2:2007-07 (E)

Wheelchair seating - Part 2: Determination of physical and mechanical characteristics of devices intended to manage tissue integrity - Seat cushions

Contents		Page
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	2
5	Apparatus	3
6	Test environment	6
7	Preparation of test cushion	7
7.1	Choice of cushion	7
7.2	Preconditioning the cushion	7
7.3	Setup	8
8	Sequence of testing	8
9	Load-deflection and hysteresis test	8
9.1	Rationale	8
9.2	Test method	8
9.3	Method of calculation	9
9.4	Test report	10
10	Frictional properties	10
10.1	Rationale	10
10.2	Test method	10
10.3	Test report	10
11	Impact damping under normal loading conditions	10
11.1	Rationale	10
11.2	Test method	10
11.3	Method of calculation	12
12	Recovery	12
12.1	Rationale	12
12.2	Test method	12
12.3	Test report	13
13	Loaded contour depth and overload deflection	13
13.1	Rationale	13
13.2	Test method	13
13.3	Method of calculation	15
13.4	Test report	15
14	Water spillage	15
14.1	Rationale	15
14.2	Test method	15
14.3	Test report	15
15	Biocompatibility	15
15.1	Rationale	15
15.2	Test method	15
15.3	Test report	15
16	Test report	16

17	Disclosure requirement	16
Annex A (normative)	Tapered uniform geometry RCLl	17
Annex B (informative)	Fire resistance considerations	19
Annex C (informative)	Horizontal and lateral stiffness	20
Bibliography		25