ISO 7176-19:2008-07 (E)

Wheelchairs - Part 19: Wheeled mobility devices for use as seats in motor vehicles

Contents

Page

Foreword iv

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Design requirements 6
4.1 Wheelchair securement 6
4.2 Occupant restraints 6
4.2.1 Wheelchair-anchored pelvic-belt restraint 6
4.2.2 Wheelchair-anchored shoulder-belt restraint 8
4.2.3 Accommodation of vehicle-anchored occupant belt restraints 9

5 Performance requirements 10
5.1 Wheelchair-anchored belt restraints 10
5.2 Frontal impact 11
5.2.1 During the test 11
5.2.2 After the test 12
5.3 Accessibility of securement points intended for use with four-point strap-type tiedowns with hook-type end-fittings 13
5.4 Accommodation of vehicle-anchored belt restraints 13

6 Identification, labelling, user instructions, warning, and disclosure requirements 13
6.1 Identification and labelling 13
6.2 Presale literature 14
6.3 User and maintenance instructions 14

7 Documentation of compliance 17
7.1 General 17
7.2 Frontal impact test 17
7.3 Design, labelling, and literature requirements 18

Annex A (normative) Method for frontal impact test 19

Annex B (normative) Geometric specifications for securement points on wheelchairs intended for attachment of four-point strap-type tiedowns 27

Annex C (normative) Method for testing accessibility of wheelchair securement points intended for attachment of four-point strap-type tiedowns 29

Annex D (normative) Methods for rating wheelchair accommodation of vehicle-anchored belt restraints 32

Annex E (informative) Guidelines for surrogate tiedown devices 37

Annex F (normative) Specifications for wheelchair universal docking interface geometry (UDIG) 38

Bibliography 43