

ISO/IEEE 11073-10406:2012-12 (E)

Health informatics - Personal health device communication - Part 10406: Device specialization - Basic electrocardiograph (ECG) (1- to 3-lead ECG)

Contents		Page
1.	Overview	1
1.1	Scope	1
1.2	Purpose	1
1.3	Context	2
2.	Normative references	2
3.	Definitions, acronyms, and abbreviations	3
3.1	Definitions	3
3.2	Acronyms and abbreviations	3
4.1	General	4
4.3	Compliance with other standards	5
5.	Basic ECG (1- to 3-lead ECG) device concepts and modalities	6
5.1	General	6
5.2	ECG waveform	6
5.3	R-R interval	6
5.4	Heart rate	7
6.	Basic ECG (1- to 3-lead ECG) domain information model	7
6.1	Overview	7
6.2	Class extensions	7
6.3	Object instance diagram	7
6.4	Types of configuration	8
6.5	Profiles	9
6.6	Medical device system object	11
6.7	Numeric objects	15
6.8	Real-time sample array objects	18
6.9	Enumeration objects	19
6.10	PM-store objects	22
6.11	Scanner objects	29
6.12	Class extension objects	32
6.13	Basic ECG (1- to 3-lead ECG) information model extensibility rules	32
7.	Basic ECG (1- to 3-lead ECG) service model	32
7.1	General	32
7.2	Object access services	32
7.3	Object access event report services	35
8.	Basic ECG (1- to 3-lead ECG) communication model	35
8.1	Overview	35
8.2	Communications characteristics	36
8.3	Association procedure	36
8.4	Configuring procedure	38
8.5	Operating procedure	39
8.6	Time synchronization	40
9.	Test associations	40
9.1	Behavior with standard configuration	40
9.2	Behavior with extended configurations	41

10.	Conformance	41
10.1	Applicability	41
10.2	Conformance specification	41
10.3	Levels of conformance	42
10.4	Implementation conformance statements	42
Annex A (informative) Bibliography		47
Annex B (normative) Any additional ASN.1 definitions		48
Annex C (normative) Allocation of identifiers		49
Annex D (informative) Message sequence examples		50
Annex E (informative) Protocol data unit examples		52