

# ISO/TR 13570-2:2014-06 (E)

## Wheelchairs - Part 2: Typical values and recommended limits of dimensions, mass and manoeuvring space as determined in ISO 7176-5

---

| <b>Contents</b>    |  | <b>Page</b> |
|--------------------|--|-------------|
| Foreword .....     |  | iv          |
| Introduction ..... |  | v           |
| <b>1</b>           | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>           | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>           | <b>Terms and definitions .....</b>   | <b>1</b>    |
| <b>4</b>           | <b>Wheelchair groups .....</b>   | <b>1</b>    |
| 4.1                | General .....  | 1           |
| 4.2                | Wheelchairs with handrims .....  | 2           |
| 4.3                | Electrically powered wheelchairs of class A .....                            | 2           |
| 4.4                | Electrically powered wheelchairs of class B .....                            | 2           |
| 4.5                | Electrically powered wheelchairs of class C .....                            | 2           |
| 4.6                | Electrically powered wheelchairs (scooter design) .....                      | 2           |
| <b>5</b>           | <b>Typical values and recommended limits for required measurements .....</b> | <b>2</b>    |
| 5.1                | General .....  | 2           |
| 5.2                | Full overall length .....  | 2           |
| 5.3                | Overall width .....  | 3           |
| 5.4                | Handgrip height .....  | 4           |
| 5.5                | Stowage length .....   | 5           |
| 5.6                | Stowage width .....  | 6           |
| 5.7                | Stowage height .....   | 7           |
| 5.8                | Rising .....   | 8           |
| 5.9                | Total mass .....   | 8           |
| 5.10               | Mass of heaviest part .....  | 9           |
| 5.11               | Pivot width .....  | 10          |
| 5.12               | Reversing width .....  | 11          |
| 5.13               | Turning diameter .....   | 12          |
| 5.14               | Ground clearance .....   | 13          |
| 5.15               | Required width of angled corridor .....                                      | 14          |
| 5.16               | Required doorway entry depth .....   | 15          |
| 5.17               | Required corridor width for side opening .....                               | 16          |
| <b>6</b>           | <b>Typical values and recommended limits for Technical dimensions .....</b>  | <b>17</b>   |
| 6.1                | Reduced overall length .....   | 17          |
| 6.2                | Overall height .....   | 18          |
| 6.3                | Radial wheel deviation for mass group I, II, and III .....                   | 18          |
| 6.4                | Lateral wheel deviation for mass group I, II, and III .....                  | 19          |
| 6.5                | Radial handrim deviation for mass I, II, and III .....                       | 19          |
| 6.6                | Lateral handrim deviation for mass I, II, and III .....                      | 20          |
| 6.7                | Full occupied length .....   | 20          |
| 6.8                | Reduced occupied length .....  | 21          |
| 6.9                | Occupied width .....   | 22          |
| 6.10               | Occupied height .....  | 23          |
| 6.11               | Ramp transition angle .....  | 23          |
| 6.12               | Wheelbase .....  | 24          |
| 6.13               | Rear wheel track .....   | 26          |

|      |   |    |
|------|---|----|
| 6.14 | Front wheel track .....   | 27 |
| 6.15 | Camber .....  | 28 |
| 6.16 | Toe of occupant mass group I, II, and III .....                       | 29 |
| 6.17 | Skew of occupant mass group I, II, and III .....                      | 30 |
| 6.18 | Castor rake of occupant mass group I, II, and III .....               | 31 |
| 6.19 | Castor cant for occupant mass group I, II, and III .....              | 32 |
| 6.20 | Castor trail for occupant mass group I, II, and III .....             | 32 |
| 6.21 | Castor wheel misalignment of occupant mass group I, II, and III ..... | 33 |