

# ISO 10555-6:2015-04 (E)

## Intravascular catheters - Sterile and single-use catheters - Part 6: Subcutaneous implanted ports

---

| <b>Contents</b>              |  | <b>Page</b> |
|------------------------------|--|-------------|
| Foreword .....               |  | iv          |
| <b>1</b>                     | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>                     | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>                     | <b>Terms and definitions .....</b>   | <b>1</b>    |
| <b>4</b>                     | <b>Requirements of the implantable subcutaneous implanted port and catheter .....</b>        | <b>3</b>    |
| 4.1                          | General .....  | 3           |
| 4.2                          | Biocompatibility .....   | 4           |
| 4.3                          | Distance markings .....  | 4           |
| 4.4                          | Nominal dimensions of the subcutaneous implanted port .....                                  | 4           |
| 4.5                          | Physical requirements .....  | 4           |
| 4.5.1                        | Radio-detectability .....  | 4           |
| 4.5.2                        | Surface finish .....   | 4           |
| 4.5.3                        | Freedom from leakage .....   | 4           |
| 4.5.4                        | Flushing volume .....  | 4           |
| 4.5.5                        | Characteristics of the septum .....  | 5           |
| 4.5.6                        | Characteristics of the connection or the catheter .....                                      | 5           |
| 4.6                          | Flow rate .....  | 5           |
| 4.6.1                        | Subcutaneous implanted ports not indicated for power injection .....                         | 5           |
| 4.6.2                        | Subcutaneous implanted ports indicated for power injection .....                             | 5           |
| 4.7                          | Burst pressure of the subcutaneous implanted port and catheter .....                         | 6           |
| 4.7.1                        | Subcutaneous implanted ports not indicated for power injection .....                         | 6           |
| 4.7.2                        | Subcutaneous implanted ports indicated for power injection .....                             | 6           |
| <b>5</b>                     | <b>Magnetic Resonance Imaging (MRI) compatibility .....</b>                                  | <b>6</b>    |
| <b>6</b>                     | <b>Information to be supplied by the manufacturer .....</b>                                  | <b>6</b>    |
| 6.1                          | Marking on the device .....  | 6           |
| 6.2                          | Primary packaging .....  | 6           |
| 6.3                          | Labels for traceability .....  | 7           |
| 6.4                          | Instruction for use .....  | 7           |
| <b>Annex A (normative)</b>   | <b>Test method for freedom from air leakage .....</b>  | <b>8</b>    |
| <b>Annex B (informative)</b> | <b>Determination of flushing volume .....</b>  | <b>10</b>   |
| <b>Annex C (informative)</b> | <b>Guidance on further characterization testing: Needle penetration and withdrawal .....</b> | <b>12</b>   |
| <b>Annex D (normative)</b>   | <b>Test method for freedom from leakage after multiple punctures .....</b>                   | <b>14</b>   |
| <b>Annex E (normative)</b>   | <b>Peak tensile force .....</b>  | <b>15</b>   |
| <b>Bibliography .....</b>    |  | <b>16</b>   |