

ISO 10555-6:2015-04 (E)

Intravascular catheters - Sterile and single-use catheters - Part 6: Subcutaneous implanted ports

Contents	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements of the implantable subcutaneous implanted port and catheter	3
4.1 General	3
4.2 Biocompatibility	4
4.3 Distance markings	4
4.4 Nominal dimensions of the subcutaneous implanted port	4
4.5 Physical requirements	4
4.5.1 Radio-detectability	4
4.5.2 Surface finish	4
4.5.3 Freedom from leakage	4
4.5.4 Flushing volume	4
4.5.5 Characteristics of the septum	5
4.5.6 Characteristics of the connection or the catheter	5
4.6 Flow rate	5
4.6.1 Subcutaneous implanted ports not indicated for power injection	5
4.6.2 Subcutaneous implanted ports indicated for power injection	5
4.7 Burst pressure of the subcutaneous implanted port and catheter	6
4.7.1 Subcutaneous implanted ports not indicated for power injection	6
4.7.2 Subcutaneous implanted ports indicated for power injection	6
5 Magnetic Resonance Imaging (MRI) compatibility	6
6 Information to be supplied by the manufacturer	6
6.1 Marking on the device	6
6.2 Primary packaging	6
6.3 Labels for traceability	7
6.4 Instruction for use	7
Annex A (normative) Test method for freedom from air leakage	8
Annex B (informative) Determination of flushing volume	10
Annex C (informative) Guidance on further characterization testing: Needle penetration and withdrawal	12
Annex D (normative) Test method for freedom from leakage after multiple punctures	14
Annex E (normative) Peak tensile force	15
Bibliography	16