

ISO 16840-6:2015-09 (E)

Wheelchair seating - Part 6: Simulated use and determination of the changes in properties of seat cushions

| Contents | Page |
|--|------------|
| Foreword | vi |
| Introduction | vii |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Symbols and abbreviated terms | 5 |
| 5 Apparatus for characterizing and ageing cushions | 5 |
| 5.1 Apparatus for characterizing cushions | 5 |
| 5.2 Apparatus for aging cushions | 6 |
| 6 Test environment | 7 |
| 7 Preparation and setup of cushion | 7 |
| 8 Selection and order of testing | 7 |
| 8.1 Testing consists of three stages | 7 |
| 9 Envelopment | 8 |
| 9.1 Rationale | 8 |
| 9.2 Test method and reporting | 8 |
| 10 Column buckling | 8 |
| 10.1 Rationale | 8 |
| 10.2 Test method | 9 |
| 10.3 Method of calculation | 9 |
| 10.4 Test report | 9 |
| 11 Heat and humidity | 9 |
| 11.1 Rationale | 9 |
| 11.2 Test method | 9 |
| 11.3 Method of calculation | 10 |
| 11.4 Test report | 10 |
| 12 Heated indenter compression set | 11 |
| 12.1 Rationale | 11 |
| 12.2 Test method | 11 |
| 12.3 Method of calculation | 11 |
| 12.4 Test report | 11 |
| 13 Impact damping under normal conditions | 12 |
| 13.1 Rationale | 12 |
| 13.2 Test method | 12 |
| 14 Interface pressure measurement test (pressure mapping) | 12 |
| 14.1 Rationale | 12 |

| | | |
|---------------|--|-----------|
| 14.2 | Test method | 12 |
| 14.3 | Method of calculation | 12 |
| 14.4 | Test report | 13 |
| 15 | Lateral stiffness | 13 |
| 15.1 | Rationale | 13 |
| 15.2 | Test method | 13 |
| 15.3 | Method of calculation | 14 |
| 15.4 | Test report | 14 |
| 16 | Leak | 14 |
| 16.1 | Rationale | 14 |
| 16.2 | Test method | 14 |
| 16.3 | Test report | 14 |
| 17 | Loadedcontourdepthandoverloaddeflection | 14 |
| 17.1 | Rationale | 14 |
| 17.2 | Test method | 15 |
| 17.3 | Method of calculation | 15 |
| 18 | Hysteresis test | 15 |
| 18.1 | Rationale | 15 |
| 18.2 | Test method | 15 |
| 19 | Sliding resistance | 15 |
| 19.1 | Rationale | 15 |
| 19.2 | Test method | 15 |
| 19.3 | Method of calculation | 15 |
| 19.4 | Test report | 16 |
| 20 | 10%forcedeflection | 16 |
| 20.1 | Rationale | 16 |
| 20.2 | Test method | 16 |
| 20.3 | Method of calculation | 16 |
| 21 | Stage 2: Simulated age testing | 16 |
| 22 | Accelerated aging | 17 |
| 22.1 | Rationale | 17 |
| 22.2 | Test method | 17 |
| 22.2.1 | 70 °C accelerated aging procedure | 17 |
| 22.2.2 | 50 °C modified accelerated aging procedure (for cushions made with hydrogels or other materials not intended for high temperature exposure) | 18 |
| 22.3 | Method of calculation | 18 |
| 22.4 | Test report | 18 |
| 23 | Bacterial soiling | 18 |
| 23.1 | Rationale | 18 |
| 23.2 | Test method | 18 |
| 23.2.1 | Preparation of bacterial soiling broth | 18 |
| 23.2.2 | Bacterial exposure | 19 |
| 23.3 | Method of calculation | 19 |
| 23.4 | Test report | 19 |
| 24 | Cold exposure | 20 |
| 24.1 | Rationale | 20 |
| 24.2 | Test method | 20 |
| 24.3 | Method of calculation | 20 |
| 24.4 | Test report | 20 |
| 25 | Cyclic loading at elevated temperature | 20 |

| | | |
|--------|---|----|
| 25.1 | Rationale | 20 |
| 25.2 | Test method | 20 |
| 25.3 | Method of calculation | 21 |
| 25.4 | Test report | 21 |
| 26 | Disinfection | 21 |
| 26.1 | Rationale | 21 |
| 26.2 | Test method | 21 |
| 26.2.1 | Cover of cushion disinfection | 21 |
| 26.2.2 | Interior cushion disinfection | 21 |
| 27 | Faecal soiling with cyclic loading | 22 |
| 27.1 | Rationale | 22 |
| 27.2 | Test method | 22 |
| 27.3 | Method of calculation | 22 |
| 27.4 | Test report | 22 |
| 28 | Heat and humidity | 22 |
| 28.1 | Rationale | 22 |
| 28.2 | Test method | 23 |
| 28.3 | Method of calculation | 23 |
| 28.4 | Test report | 23 |
| 29 | Laundering | 23 |
| 29.1 | Rationale | 23 |
| 29.2 | Test method | 23 |
| 29.2.1 | Cover of cushion laundering | 23 |
| 29.2.2 | Interior cushion laundering | 23 |
| 29.3 | Method of calculation | 23 |
| 29.4 | Test report | 23 |
| 30 | Urinary soiling with cyclic loading | 24 |
| 30.1 | Rationale | 24 |
| 30.2 | Test method | 24 |
| 30.3 | Method of calculation | 24 |
| 30.4 | Test report | 24 |
| 31 | UV and ozone exposure | 24 |
| 31.1 | Rationale | 24 |
| 31.2 | Test method | 24 |
| 31.3 | Method of calculation | 25 |
| 31.4 | Test report | 25 |
| 32 | Stage 3: Post-aged cushion testing | 25 |
| 33 | Method of calculations | 25 |
| 34 | Test report | 26 |
| | Annex A (informative)Influences that drive changes in seat cushion performance | 27 |
| | Bibliography | 28 |