

DIN EN ISO 10555-6:2017-11 (E)

Intravascular catheters - Sterile and single-use catheters - Part 6: Subcutaneous implanted ports (ISO 10555-6:2015)

Contents		Page
European foreword		3
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 93/42/EEC [OJ L 169] aimed to be covered		5
Foreword		8
1	Scope	9
2	Normative references	9
3	Terms and definitions	9
4	Requirements of the implantable subcutaneous implanted port and catheter	11
4.1	General.....	11
4.2	Biocompatibility.....	12
4.3	Distance markings.....	12
4.4	Nominal dimensions of the subcutaneous implanted port.....	12
4.5	Physical requirements.....	12
4.5.1	Radio-detectability.....	12
4.5.2	Surface finish.....	12
4.5.3	Freedom from leakage.....	12
4.5.4	Flushing volume.....	12
4.5.5	Characteristics of the septum.....	13
4.5.6	Characteristics of the connection or the catheter.....	13
4.6	Flow rate.....	13
4.6.1	Subcutaneous implanted ports not indicated for power injection.....	13
4.6.2	Subcutaneous implanted ports indicated for power injection.....	13
4.7	Burst pressure of the subcutaneous implanted port and catheter.....	14
4.7.1	Subcutaneous implanted ports not indicated for power injection.....	14
4.7.2	Subcutaneous implanted ports indicated for power injection.....	14
5	Magnetic Resonance Imaging (MRI) compatibility	14
6	Information to be supplied by the manufacturer	14
6.1	Marking on the device.....	14
6.2	Primary packaging.....	14
6.3	Labels for traceability.....	15
6.4	Instruction for use.....	15
Annex A (normative) Test method for freedom from air leakage		16
Annex B (informative) Determination of flushing volume		17
Annex C (informative) Guidance on further characterization testing: Needle penetration and withdrawal		19
Annex D (normative) Test method for freedom from leakage after multiple punctures		21
Annex E (normative) Peak tensile force		22
Bibliography		23