ISO 20698:2018 (E)

Catheter systems for neuraxial application — Sterile and single-use catheters and accessories

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Intended performance

5 Design attributes

5.1 Nominal size of the catheter
5.1.1 General
5.1.2 Outside diameter
5.1.3 Catheter lengths
5.2 Catheter holes
5.3 Distal tip
5.4 Surface
5.5 Hubs
5.6 Markings
5.7 Filter
5.8 Stylet
5.9 Detectability
5.10 Fixation devices

6 Materials

6.1 General
6.2 Biocompatibility
6.3 Drug and material compatibility

7 Design evaluation

7.1 General
7.2 Pre-clinical evaluation
7.2.1 General
7.2.2 Radiopacity
7.2.3 Magnetic resonance compatibility
7.2.4 Corrosion resistance
7.2.5 Flow rate
7.2.6 Freedom from leakage (design)
7.2.7 Peak tensile force
7.2.8 Catheter kinking test
7.2.9 Surface
7.3 Clinical evaluation

8 Sterilization

8.1 General
8.2 Sterilization residuals

9 Packaging

10 Information to be supplied by the manufacturer

10.1 Marking on the device
10.2 Information on instructions for use and/or packaging

Annex A (normative) Test method for resistance to corrosion

A.1 Principle
A.2 Reagents
A.3 Apparatus
A.4 Procedure
A.5 Test report

Annex B (normative) Determination of flow rate through catheter

B.1 Principle
B.2 Reagent
B.3 Apparatus
B.4 Procedure
B.5 Expression of results
B.6 Test report

Annex C (normative) Test method for liquid leakage under pressure

C.1 Principle
C.2 Reagents
C.3 Apparatus
C.4 Procedure
C.5 Test report

Annex D (normative) Method for determining peak tensile force

D.1 Principle
D.2 Apparatus
D.3 Procedure
D.4 Test report

Annex E (informative) Other units of measurement

E.1 General
E.2 French or Charrière
E.3 Needle gauge

Page count: 20