ISO 23599:2019 (E)

Assistive products for blind and vision-impaired persons — Tactile walking surface indicators

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 General provisions

4.1 General principles
4.2 Detecting and distinguishing TWSIs
4.2.1 General
4.2.2 Tactile contrast
4.2.3 Visual contrast
4.2.4 Design for prevention of tripping

5 Requirements and recommendations

5.1 Specifications for shape and dimensions of TWSIs
5.1.1 General
5.1.2 Attention patterns
5.1.2.1 Arrangements
5.1.2.2 Height
5.1.2.3 Diameter
5.1.2.4 Spacing
5.1.3 Guiding patterns
5.1.3.1 Arrangements
5.1.3.2 Specifications for flat-topped elongated bars
5.1.3.2.1 Height
5.1.3.2.2 Width
5.1.3.2.3 Spacing
5.1.3.2.4 Length
5.1.3.2.5 Continuity
5.1.3.3 Specifications for sinusoidal rib pattern
5.1.3.3.1 Height of wave crests
5.1.3.3.2 Spacing between wave crests
5.1.3.3.3 Length of sinusoidal ribs
5.2 Surrounding or adjacent surfaces
5.3 Visual contrast
5.3.1 General
5.3.2 Luminance contrast
5.3.3 Calculation of the luminance contrast value
5.3.4 Maintenance of minimum luminance contrast
5.3.5 Measurement condition
5.3.6 Difference in colour or tone
5.3.7 Illumination
5.4 Materials
5.5 Installation
5.5.1 General
5.5.2 Principles for installation of TWSIs
5.5.3 Principles for installation of attention patterns
5.5.4 Principles for installation of guiding patterns

Annex A (informative) Luminance contrast

A.1 Formula for calculating luminance contrast
A.2 Methods for measuring the parameters required to calculate luminance contrast
A.2.1 General
A.2.2 Measurement with non-contact-type instruments
A.2.3 Measurement with contact-type instruments

Annex B (informative) Examples of installations of TWSIs in specific situations

B.1 General
B.2 Pedestrian crossings
B.3 At-grade kerbs
B.4 Railway platforms
B.5 Stairs
B.6 Ramps
B.7 Escalators and travelators
B.8 Elevators
B.9 Revolving doors

Page count: 41