

DIN EN ISO 10555-6:2020-02 (E)

Intravascular catheters - Sterile and single-use catheters - Part 6: Subcutaneous implanted ports (ISO 10555-6:2015 + Amd 1:2019) (includes Amendment A1:2019)

Contents	Page
European foreword.....	3
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 93/42/EEC [O] L 169] aimed to be covered	4
[A1] European foreword to Amendmant A1 [A1]	7
Foreword	8
[A1] Foreword to Amendmant A1 [A1]	9
1 Scope	10
2 Normative references	10
3 Terms and definitions	10
4 Requirements of the implantable subcutaneous implanted port and catheter	12
4.1 General.....	12
4.2 Biocompatibility.....	13
4.3 Distance markings.....	13
4.4 Nominal dimensions of the subcutaneous implanted port.....	13
4.5 Physical requirements.....	13
4.5.1 Radio-detectability.....	13
4.5.2 Surface finish.....	13
4.5.3 Freedom from leakage.....	13
4.5.4 Flushing volume.....	13
4.5.5 Characteristics of the septum.....	14
4.5.6 Characteristics of the connection or the catheter.....	14
4.6 Flow rate.....	14
4.6.1 Subcutaneous implanted ports not indicated for power injection.....	14
4.6.2 Subcutaneous implanted ports indicated for power injection.....	14
4.7 Burst pressure of the subcutaneous implanted port and catheter.....	15
4.7.1 Subcutaneous implanted ports not indicated for power injection.....	15
4.7.2 Subcutaneous implanted ports indicated for power injection.....	15
5 Magnetic Resonance Imaging (MRI) compatibility	15
6 Information to be supplied by the manufacturer	15
6.1 Marking on the device.....	15
6.2 Primary packaging.....	15
6.3 Labels for traceability.....	16
6.4 Instruction for use.....	16
Annex A (normative) Test method for freedom from air leakage	17
Annex B (informative) Determination of flushing volume	18
Annex C (informative) Guidance on further characterization testing: Needle penetration and withdrawal	20
Annex D (normative) Test method for freedom from leakage after multiple punctures	22
Annex E (normative) Peak tensile force	23
Bibliography	24