ISO 7886-2:2020-04 (E)

Sterile hypodermic syringes for single use - Part 2: Syringes for use with power-driven syringe pumps

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Nomenclature **1**

5 General requirements **2**

6 Limits for acidity or alkalinity **2**

7 Limits for extractable metals **2**

8 Lubricant **2**

9 Tolerance on graduated capacity **2**

10 Graduated scale **2**

11 Syringe design **2**

12 Piston/plunger assembly **4**
12.1 Design 4
12.2 Fit of plunger stopper/plunger in barrel 4

13 Nozzle **4**
13.1 Conical fitting 4
13.2 Nozzle lumen 4

14 Performance **4**
14.1 Dead space 4
14.2 Freedom from air and liquid leakage past the plunger stopper 4
14.3 Short-term flow rate error 4
14.4 Pump forces 5
14.5 Syringe compliance 5

15 Packaging **6**
15.1 Unit packaging and self-contained syringe units 6
15.1.1 Unit packaging 6
15.1.2 Self-contained syringe units 6
15.2 Multiple unit pack 6
15.3 User packaging 6

16 Information supplied by the manufacturer **6**
16.1 General 6
16.2 Syringes 6
16.2.1 General 6
16.2.2 Additional marking for self-contained syringe units 7
16.3 Unit packaging 7
16.4 Multiple unit packs 7
16.4.1 General 7
16.4.2 Multiple unit packs with self-contained syringes 7
16.5 User packaging 7
16.6 Storage container 7
16.7 Transport wrapping 7

Annex A (normative) **Short-term flow rate accuracy** **8**
Annex B (informative) **Pump force** **13**
Annex C (normative) **Determination of syringe compliance** **15**
Bibliography **17**