

ISO 7886-2:2020-04 (E)

Sterile hypodermic syringes for single use - Part 2: Syringes for use with power-driven syringe pumps

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Nomenclature	1
5	General requirements	2
6	Limits for acidity or alkalinity	2
7	Limits for extractable metals	2
8	Lubricant	2
9	Tolerance on graduated capacity	2
10	Graduated scale	2
11	Syringe design	2
12	Piston/plunger assembly	4
	12.1 Design	4
	12.2 Fit of plunger stopper/plunger in barrel	4
13	Nozzle	4
	13.1 Conical fitting	4
	13.2 Nozzle lumen	4
14	Performance	4
	14.1 Dead space	4
	14.2 Freedom from air and liquid leakage past the plunger stopper	4
	14.3 Short-term flow rate error	4
	14.4 Pump forces	5
	14.5 Syringe compliance	5
15	Packaging	6
	15.1 Unit packaging and self-contained syringe units	6
	15.1.1 Unit packaging	6
	15.1.2 Self-contained syringe units	6
	15.2 Multiple unit pack	6
	15.3 User packaging	6
16	Information supplied by the manufacturer	6
	16.1 General	6
	16.2 Syringes	6
	16.2.1 General	6
	16.2.2 Additional marking for self-contained syringe units	7
	16.3 Unit packaging	7
	16.4 Multiple unit packs	7
	16.4.1 General	7
	16.4.2 Multiple unit packs with self-contained syringes	7
	16.5 User packaging	7
	16.6 Storage container	7
	16.7 Transport wrapping	7

Annex A (normative) Short-term flow rate accuracy	8
Annex B (informative) Pump force	13
Annex C (normative) Determination of syringe compliance	15
Bibliography	17