

ISO 7886-3:2020-05 (E)

Sterile hypodermic syringes for single use - Part 3: Auto-disabled syringes for fixed-dose immunization

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Nomenclature | 2 |
| 5 | General requirements | 3 |
| 6 | Extraneous matter | 4 |
| 6.1 | General | 4 |
| 6.2 | Limits for acidity or alkalinity | 4 |
| 6.3 | Limits for extractable metals | 4 |
| 7 | Lubricant | 4 |
| 8 | Tolerance on nominal capacity | 4 |
| 9 | Graduated scale | 5 |
| 9.1 | Scale | 5 |
| 9.2 | Position of scale | 5 |
| 10 | Barrel | 5 |
| 10.1 | Dimensions | 5 |
| 10.2 | Barrel flanges | 5 |
| 11 | Plunger stopper/plunger assembly | 5 |
| 11.1 | Design | 5 |
| 11.2 | Fit of the plunger stopper/plunger in the barrel | 6 |
| 11.3 | Fiducial line | 6 |
| 12 | Needle | 6 |
| 12.1 | General | 6 |
| 12.2 | Integrated needle | 6 |
| 12.3 | Non-integrated needle | 6 |
| 12.4 | Sharps protection features | 6 |
| 13 | Performance | 7 |
| 13.1 | General | 7 |
| 13.2 | Dead space | 7 |
| 13.3 | Freedom from air and liquid leakage | 7 |
| 13.4 | Auto-disable syringe feature | 7 |
| 13.5 | Performance after shipping | 7 |
| 14 | Packaging | 8 |
| 14.1 | Unit packaging providing sterile barrier | 8 |

| | | |
|--|--|----|
| 14.2 | Multiple unit pack | 8 |
| 14.3 | User packaging | 8 |
| 15 | Information supplied by the manufacturer | 8 |
| 15.1 | General | 8 |
| 15.2 | Syringes | 8 |
| 15.3 | Unit packaging providing sterile barrier | 8 |
| 15.4 | User packaging | 9 |
| 15.5 | Storage containers | 9 |
| 15.6 | Transport wrapping | 10 |
| Annex A (normative) Method for preparation of extracts | | 11 |
| Annex B (informative) Test method for forces required to operate piston | | 12 |
| Annex C (normative) Test method for testing auto-disable syringe feature | | 14 |
| Bibliography | | 15 |