

# ISO 11608-4:2022-04 (E)

## Needle-based injection systems for medical use - Requirements and test methods - Part 4: Needle-based injection systems containing electronics

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	3
4	Abbreviated terms .....	11
5	General requirements .....	11
5.1	Conditions for application of NIS-E .....	11
5.2	General design requirements .....	12
5.3	Risk approach and usability engineering .....	12
6	General requirements for testing .....	13
6.1	Type tests .....	13
6.2	Number of samples .....	13
6.3	Ambient temperature, humidity, atmospheric pressure .....	18
7	Identification and marking of NIS-E .....	18
8	Protection against electrical hazards .....	18
8.1	General .....	18
8.2	Humidity preconditioning treatment .....	18
8.3	Requirements and test methods .....	19
8.3.1	General .....	19
8.3.2	Applied parts .....	19
8.3.3	Requirements related to power sources .....	21
8.3.4	Limitation of current for accessible parts and applied parts .....	22
8.4	Separation of parts (Type X and Type Y) .....	22
8.4.1	Means of protection (MOP) .....	22
8.4.2	Separation of patient connection .....	23
8.4.3	Maximum mains voltage .....	24
8.4.4	Working voltage .....	24
8.5	Patient leakage current and touch current (Type X and Type Y NIS-E) .....	25
8.5.1	General .....	25
8.5.2	Measurement of patient leakage current .....	29
8.5.3	Measurement of touch current .....	32
8.6	Insulation (Type X and Type Y) .....	33
8.6.1	General .....	33
8.6.2	Distance through solid insulation or use of thin sheet material .....	33
8.6.3	Dielectric strength .....	34
8.7	Insulation other than wire insulation .....	34
8.7.1	Mechanical strength and resistance to heat .....	34
8.8	Creepage distances and air clearances (Type X and Type Y NIS-E) .....	35
8.8.1	General .....	35
8.9	Specific hazardous situations .....	36
8.9.1	General .....	36

8.9.2	Emissions, deformation of enclosure or exceeding maximum temperature .....	36
8.9.3	Exceeding leakage current or voltage limits .....	38
8.9.4	Specific mechanical hazards .....	38
8.10	Single fault conditions (Type X and Type Y) .....	38
8.10.1	General .....	38
8.10.2	Failure of thermostats and temperature limiting devices .....	38
8.10.3	Leakage of liquid from batteries .....	39
8.10.4	Locking of moving parts .....	39
8.10.5	Additional test criteria for motor-operated NIS-E .....	39
<b>ISO 11608-4:2022(E) 8.10.6 NIS-E intended for used in conjunction with oxygen rich environments</b> .....		<b>39</b>
8.10.7	Power supply (Type Y) .....	39
8.11	Pre-conditioning for the influence of fluid leakage .....	40
<b>9</b>	<b>Electromagnetic compatibility (EMC) .....</b>	<b>41</b>
9.1	General requirements .....	41
9.1.1	Risk approach process for NIS-E .....	41
9.1.2	Non-medical electrical equipment used with NIS-E .....	41
9.1.3	General test conditions .....	42
9.2	NIS-E identification, marking and documents .....	47
9.2.1	Instruction for use in relation to EMC .....	47
9.2.2	Documentation of the tests .....	47
9.3	Electromagnetic emissions requirements for NIS-E .....	48
9.3.1	Protection of radio services and other equipment .....	48
9.3.2	Protection of the public mains network .....	48
9.3.3	Emissions requirements summary (Type X and Type Y) .....	49
9.4	Electromagnetic immunity requirements for NIS-E .....	49
9.4.1	General .....	49
9.4.2	Operating modes .....	51
9.4.3	Non-medical electrical equipment .....	51
9.4.4	Immunity test levels .....	51
9.4.5	Immunity to proximity fields from RF wireless communications equipment .....	56
9.4.6	Immunity to proximity magnetic fields in the frequency range 9 kHz to 13,56 MHz .....	58
<b>10</b>	<b>Protection against mechanical hazards .....</b>	<b>58</b>
10.1	General .....	58
10.2	Shock .....	58
10.3	Vibration .....	58
10.3.1	Sinusoidal vibration .....	58
10.3.2	Random vibration .....	58
10.4	Impact of OBDS enclosures .....	59
10.5	Push .....	59
<b>11</b>	<b>Programmable NIS-E .....</b>	<b>59</b>
<b>Annex A (informative) Identification of immunity pass/fail criteria .....</b>		<b>60</b>
<b>Annex B (informative) Rationale for using 240 V for testing some requirements .....</b>		<b>62</b>
<b>Bibliography .....</b>		<b>63</b>