

DIN EN ISO 11608-5:2023-05 (E)

Needle-based injection systems for medical use - Requirements and test methods - Part 5: Automated functions (ISO 11608-5:2022)

| Contents | | Page |
|--|-------|-------------|
| European foreword | | 3 |
| Foreword | | 4 |
| Introduction | | 5 |
| 1 Scope | | 6 |
| 2 Normative references | | 6 |
| 3 Terms and definitions | | 7 |
| 4 Requirements | | 9 |
| 4.1 General requirements | | 9 |
| 4.2 Medicinal product preparation | | 10 |
| 4.3 Needle preparation | | 11 |
| 4.4 Needle hiding | | 11 |
| 4.5 Priming | | 11 |
| 4.6 Dose setting | | 11 |
| 4.7 Needle insertion | | 11 |
| 4.8 Injection depth control | | 11 |
| 4.9 Dose delivery | | 12 |
| 4.10 Recording of device functions | | 12 |
| 4.11 Needle retraction | | 12 |
| 4.11.1 Completion of dose delivery | | 12 |
| 4.11.2 Needle retraction distance | | 12 |
| 4.11.3 Communication of completion | | 12 |
| 4.12 Disabling the NIS-AUTO | | 12 |
| 4.13 Needle shielding | | 13 |
| 4.13.1 General | | 13 |
| 4.13.2 Needle shielding before injection | | 13 |
| 4.13.3 Needle shielding after injection | | 13 |
| 4.14 Needle removal from the NIS-AUTO | | 13 |
| 5 Test methods | | 13 |
| 5.1 General | | 13 |
| 5.2 Test conditions | | 14 |
| 5.3 Actuation | | 14 |
| 5.4 Medicinal product preparation | | 14 |
| 5.5 Needle inspection | | 14 |
| 5.6 Needle hiding | | 14 |
| 5.7 Priming | | 15 |
| 5.8 Needle extension | | 15 |
| 5.9 Injection time | | 15 |
| 5.10 Dose accuracy | | 16 |
| 5.11 Retracted position | | 16 |
| 5.12 Disabling the NIS-AUTO | | 16 |
| 5.13 Needle shielding | | 16 |
| 5.13.1 Needle shielding before and after injection | | 16 |
| 5.13.2 Needle shielding after free fall | | 16 |
| 6 Information supplied with the NIS-AUTO | | 16 |

| | |
|---|-----------|
| Annex A (informative) Rationale for requirements | 17 |
| Annex B (informative) Example of a test method for dose accuracy at intended injection depth | 19 |
| Annex C (informative) Needle extension and intended injection depth | 21 |
| Bibliography | 27 |