

ISO 8637-2:2024-04 (E)

Extracorporeal systems for blood purification - Part 2: Extracorporeal blood and fluid circuits for haemodialysers, haemodiafilters, haemofilters and haemoconcentrators

| Contents | | Page |
|---------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Requirements | 6 |
| 4.1 | General | 6 |
| 4.2 | Biological safety and haemocompatibility | 6 |
| 4.3 | Sterility | 6 |
| 4.4 | Non-pyrogenicity | 7 |
| 4.5 | Mechanical characteristics | 7 |
| 4.5.1 | Structural integrity | 7 |
| 4.5.2 | Connectors to haemodialyser, haemodiafilter or haemofilter | 7 |
| 4.5.3 | Connectors to vascular access device | 10 |
| 4.5.4 | Connectors to ancillary components | 10 |
| 4.5.5 | Colour coding | 10 |
| 4.5.6 | Access ports | 10 |
| 4.5.7 | Blood pathway volume | 11 |
| 4.5.8 | Air capture chamber fill level | 11 |
| 4.5.9 | Transducer protectors | 11 |
| 4.6 | Functional characteristics | 11 |
| 4.6.1 | General | 11 |
| 4.6.2 | Blood pump system performance | 11 |
| 4.6.3 | Dialysis fluid pump performance | 12 |
| 4.6.4 | Net fluid removal | 12 |
| 4.6.5 | Substitution fluid flow rate | 12 |
| 4.6.6 | Dialysis fluid composition | 12 |
| 4.6.7 | Dialysis fluid temperature | 12 |
| 4.6.8 | Substitution fluid temperature | 12 |
| 4.6.9 | Fluid path occlusion | 12 |
| 4.6.10 | Prevention of air infusion | 13 |
| 4.6.11 | Pressure monitoring | 13 |
| 4.6.12 | Blood leak detection | 13 |
| 4.7 | Expiry date | 13 |
| 5 | Test methods | 13 |
| 5.1 | General | 13 |
| 5.2 | Biological safety and haemocompatibility | 14 |
| 5.3 | Sterility | 14 |
| 5.4 | Non-pyrogenicity | 14 |
| 5.5 | Mechanical characteristics | 14 |
| 5.5.1 | Structural integrity | 14 |
| 5.5.2 | Connectors to haemodialyser, haemodiafilter or haemofilter | 15 |
| 5.5.3 | Connectors to vascular access device | 20 |
| 5.5.4 | Connectors to ancillary components | 20 |
| 5.5.5 | Colour coding | 20 |
| 5.5.6 | Access ports | 21 |
| 5.5.7 | Blood pathway volume | 21 |

| | | |
|----------|---|-----------|
| 5.5.8 | Air capture chamber fill level | 21 |
| 5.5.9 | Transducer protectors | 21 |
| 5.6 | Functional characteristics | 22 |
| 5.6.1 | General | 22 |
| 5.6.2 | Blood pump system performance | 22 |
| 5.6.3 | Dialysis fluid pump performance | 22 |
| 5.6.4 | Net fluid removal | 22 |
| 5.6.5 | Substitution fluid flow rate | 22 |
| 5.6.6 | Dialysis fluid composition | 22 |
| 5.6.7 | Dialysis fluid temperature | 22 |
| 5.6.8 | Substitution fluid temperature | 22 |
| 5.6.9 | Fluid path occlusion | 23 |
| 5.6.10 | Prevention of air infusion | 23 |
| 5.6.11 | Pressure monitoring | 23 |
| 5.6.12 | Blood leak detection | 23 |
| 5.7 | Expiry date | 23 |
| 6 | Labelling | 23 |
| 6.1 | Labelling on the device | 23 |
| 6.2 | Labelling on unit protective packaging | 23 |
| 6.3 | Labelling on the outer shipping container | 24 |
| 6.4 | Information to be given in the accompanying documentation | 24 |
| 7 | Packaging | 26 |
| | Bibliography | 27 |