

ISO 16840-6:2026-01 (E)

Wheelchair seating - Part 6: Determination of changes in properties of seat cushions following simulated use

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | vi |
| Introduction | | vii |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviated terms | 3 |
| 5 | Apparatus for characterizing and ageing cushions | 3 |
| 5.1 | General | 3 |
| 5.2 | Apparatus for characterizing cushions | 3 |
| 5.3 | Apparatus for ageing cushions | 4 |
| 6 | Test environment | 5 |
| 7 | Preparation and setup of cushion | 6 |
| 8 | Selection and order of testing | 6 |
| 9 | Envelopment | 6 |
| 9.1 | Rationale | 6 |
| 9.2 | Test method and reporting | 6 |
| 10 | Column buckling | 7 |
| 10.1 | Rationale | 7 |
| 10.2 | Test method | 7 |
| 10.3 | Method of calculation | 7 |
| 10.4 | Test report | 7 |
| 11 | Heat and humidity | 8 |
| 11.1 | Rationale | 8 |
| 11.2 | Test method | 8 |
| 11.3 | Method of calculation | 9 |
| 11.4 | Test report | 9 |
| 12 | Heated indenter compression set | 10 |
| 12.1 | Rationale | 10 |
| 12.2 | Test method | 10 |
| 12.3 | Method of calculation | 10 |
| 12.4 | Test report | 10 |
| 13 | Impact damping under normal conditions | 11 |
| 13.1 | Rationale | 11 |
| 13.2 | Test method | 11 |
| 14 | Interface pressure measurement test (pressure mapping) | 11 |
| 14.1 | Rationale | 11 |

| | | |
|--------|--|----|
| 14.2 | Test method | 11 |
| 14.3 | Method of calculation | 11 |
| 14.4 | Test report | 12 |
| 15 | Lateral and forward stiffness | 12 |
| 15.1 | Rationale | 12 |
| 15.2 | Test method | 13 |
| 15.3 | Test report | 13 |
| 16 | Leak | 13 |
| 16.1 | Rationale | 13 |
| 16.2 | Test method | 13 |
| 16.3 | Test report | 13 |
| 17 | Loaded contour depth and overload deflection | 13 |
| 17.1 | Rationale | 13 |
| 17.2 | Test method | 14 |
| 17.3 | Method of calculation | 14 |
| 18 | Hysteresis test | 14 |
| 18.1 | Rationale | 14 |
| 18.2 | Test method | 14 |
| 19 | Sliding resistance | 14 |
| 19.1 | Rationale | 14 |
| 19.2 | Test method | 14 |
| 19.3 | Test report | 14 |
| 20 | 10% forced deflection | 15 |
| 20.1 | Rationale | 15 |
| 20.2 | Test method | 15 |
| 20.3 | Test report | 15 |
| 21 | Stage 2: Simulated ageing | 15 |
| 22 | Accelerated ageing | 16 |
| 22.1 | Rationale | 16 |
| 22.2 | Test method | 16 |
| 22.2.1 | 70 °C accelerated ageing procedure | 16 |
| 22.2.2 | 50 °C modified accelerated ageing procedure (for cushions made with hydrogels or other materials not intended for high temperature exposure) | 16 |
| 22.3 | Method of calculation | 17 |
| 22.4 | Test report | 17 |
| 23 | Bacterial soiling with cyclic loading | 17 |
| 23.1 | Rationale | 17 |
| 23.2 | Test method | 17 |
| 23.2.1 | Preparation of bacterial soiling broth | 17 |
| 23.2.2 | Bacterial exposure | 18 |
| 23.3 | Method of calculation | 18 |
| 23.4 | Test report | 18 |
| 24 | Cold exposure | 18 |
| 24.1 | Rationale | 18 |
| 24.2 | Test method | 18 |
| 24.3 | Method of evaluation | 19 |
| 24.4 | Test report | 19 |
| 25 | Cyclic loading | 19 |
| 25.1 | Rationale | 19 |
| 25.2 | Test method | 19 |

| | | |
|---|---|----|
| 25.3 | Method of calculation | 19 |
| 25.4 | Test report | 20 |
| 26 | Disinfection | 20 |
| 26.1 | Rationale | 20 |
| 26.2 | Test method | 20 |
| 26.2.1 | General | 20 |
| 26.2.2 | Disinfection of cushion cover | 20 |
| 26.2.3 | Disinfection of internal cushion | 20 |
| 27 | Faecal soiling with cyclic loading | 20 |
| 27.1 | Rationale | 20 |
| 27.2 | Test method | 20 |
| 27.3 | Method of calculation | 21 |
| 27.4 | Test report | 21 |
| 28 | Heat and humidity | 21 |
| 28.1 | Rationale | 21 |
| 28.2 | Test method | 21 |
| 28.3 | Method of calculation | 21 |
| 28.4 | Test report | 21 |
| 29 | Laundering | 22 |
| 29.1 | Rationale | 22 |
| 29.2 | Test method | 22 |
| 29.2.1 | General | 22 |
| 29.2.2 | Laundering cushion cover | 22 |
| 29.2.3 | Laundering internal cushion | 22 |
| 29.3 | Method of calculation | 22 |
| 29.4 | Test report | 22 |
| 30 | Urinary soiling with cyclic loading | 22 |
| 30.1 | Rationale | 22 |
| 30.2 | Test method | 23 |
| 30.3 | Method of calculation | 23 |
| 30.4 | Test report | 23 |
| 31 | UV and ozone exposure | 23 |
| 31.1 | Rationale | 23 |
| 31.2 | Test method | 23 |
| 31.3 | Method of calculation | 24 |
| 31.4 | Test report | 24 |
| 32 | Stage 3: Post-aged cushion testing | 24 |
| 33 | Method of calculations | 24 |
| 34 | Test report | 24 |
| Annex A (informative) Influences that drive changes in seat cushion performance | | 26 |
| Bibliography | | 27 |