

ISO/IEEE 11073-30200:2004-12 (E)

Health informatics — Point-of-care medical device communication — Part 30200: Transport profile — Cable connected

CONTENTS

1.	Overview	1
1.1	Scope	2
1.2	Purpose	2
1.3	Standards compatibility	2
1.4	Audience	2
2.	References	2
3.	Definitions, acronyms, and abbreviations	4
3.1	Definitions	4
3.2	Acronyms and abbreviations	6
4.	Goals for this standard	7
5.	Architecture	7
5.1	Topology	7
5.2	Layering	9
6.	Physical layer	9
7.	Data link layer	10
7.1	IrLAP frame	10
7.2	Procedure model	11
7.3	Minimum data link layer requirements	12
8.	Network layer	15
8.1	Discovery information	15
8.2	Information access requirements	17
8.3	Minimum IrLMP multiplexer requirements	19
9.	Transport layer	20
9.1	Maximum transfer unit	20
9.2	Transport service requirements	21
9.3	MDDL service	22
10.	Time synchronization	22
11.	Labeling and conformance requirements	23
11.1	Labeling requirements	23
11.2	Conformance requirements	23
	Annex A (normative) Physical layer	24
	Annex B (informative) Maximum cable length	35
	Annex C (informative) Modular connectors	37

Annex D (informative) RJ-45 to DB-9 modular adapters	39
Annex E (informative) Detailed rationale for pin assignments	40
Annex F (informative) 10BASE-T	41
Annex G (informative) Power delivery considerations	42
Annex H (informative) Nonisolated BCC and DCC design examples	43
Annex I (informative) Isolated BCC design example.....	45
Annex J (informative) Optical isolator design example	47
Annex K (informative) Marking guidelines	49
Annex L (informative) IrDA message examples	52
Annex M (normative) IrDA profile	58
Annex N (informative) Time synchronization using SNTP.....	61
Annex O (informative) Bibliography	69