

# DIN ISO 15759:2006-05 (E)

## Medical infusion equipment - Plastics caps with inserted elastomeric liner for containers manufactured by the blow-fill-seal (BFS) process (ISO 15759:2005)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		2
Introduction .....		2
<b>1</b>	<b>Scope .....</b>	<b>3</b>
<b>2</b>	<b>Normative references .....</b>	<b>3</b>
<b>3</b>	<b>Dimensions and designation .....</b>	<b>4</b>
<b>3.1</b>	<b>Plastics cap for attachment by welding technique (Form A) .....</b>	<b>4</b>
<b>3.2</b>	<b>Plastics cap for attachment by collar technique (Form B) .....</b>	<b>5</b>
<b>3.3</b>	<b>Elastomeric liner .....</b>	<b>6</b>
<b>4</b>	<b>Materials for cap and liner .....</b>	<b>6</b>
<b>5</b>	<b>Plastics cap -- Physical requirements and testing .....</b>	<b>7</b>
<b>5.1</b>	<b>Leak-resistance test .....</b>	<b>7</b>
<b>5.2</b>	<b>Opening force .....</b>	<b>7</b>
<b>6</b>	<b>Liner -- Physical requirements and testing .....</b>	<b>7</b>
<b>6.1</b>	<b>General requirements .....</b>	<b>7</b>
<b>6.2</b>	<b>Hardness .....</b>	<b>7</b>
<b>6.3</b>	<b>Fragmentation (coring) .....</b>	<b>7</b>
<b>6.4</b>	<b>Penetration force .....</b>	<b>7</b>
<b>6.5</b>	<b>Dynamic spike-retention capability .....</b>	<b>7</b>
<b>6.6</b>	<b>Static spike-retention capability of the liner and leak resistance of the piercing area .....</b>	<b>7</b>
<b>6.7</b>	<b>Resealability .....</b>	<b>7</b>
<b>7</b>	<b>Plastics cap -- Chemical requirements and testing .....</b>	<b>7</b>
<b>8</b>	<b>Liner -- Chemical requirements and testing .....</b>	<b>8</b>
<b>9</b>	<b>Biological requirements for plastics cap and liner .....</b>	<b>8</b>
<b>10</b>	<b>Packaging .....</b>	<b>8</b>
<b>11</b>	<b>Storage .....</b>	<b>8</b>
<b>12</b>	<b>Marking .....</b>	<b>8</b>
<b>Annex A (normative)</b>	<b>Leak-resistance test .....</b>	<b>9</b>
<b>Annex B (normative)</b>	<b>Opening force needed to expose the piercing area .....</b>	<b>10</b>
<b>Annex C (normative)</b>	<b>Fragmentation (coring) .....</b>	<b>11</b>
<b>Annex D (normative)</b>	<b>Penetration force .....</b>	<b>12</b>
<b>Annex E (normative)</b>	<b>Dynamic spike retention capability .....</b>	<b>14</b>

<b>Annex F (normative) Static spike-retention capability of the liner and leak resistance of the piercing area .....</b>	<b>15</b>
<b>Annex G (normative) Resealability .....</b>	<b>16</b>
<b>Annex H (normative) Holding device for elastomeric liner .....</b>	<b>17</b>
<b>Annex I (normative) Reference spike .....</b>	<b>18</b>
<b>Bibliography .....</b>	<b>19</b>