

DIN EN 12183:2009-12 (E)

Manual wheelchairs - Requirements and test methods

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Test apparatus | 7 |
| 5 | General requirements | 8 |
| 6 | Design requirements | 9 |
| 6.1 | Foot supports, lower leg supports and arm supports | 9 |
| 6.2 | Pneumatic tyres | 9 |
| 6.3 | Fitting an anterior pelvic support | 9 |
| 6.4 | Wheelchairs for use as seats in motor vehicles | 9 |
| 6.5 | Braking systems | 9 |
| 6.6 | Component mass | 9 |
| 6.7 | Operations intended to be carried out by the occupant and/or assistant | 9 |
| 6.8 | Operator controls | 10 |
| 6.9 | Push handles and handgrips | 10 |
| 7 | Performance requirements | 11 |
| 7.1 | General | 11 |
| 7.2 | Foot supports, lower leg support assemblies and arm supports | 11 |
| 7.3 | Static, impact and fatigue strength | 12 |
| 7.4 | Braking system | 12 |
| 7.5 | Fatigue strength of manually operated parking brakes | 14 |
| 7.6 | Operating force | 15 |
| 7.7 | Push handles and handgrips | 15 |
| 7.8 | Static stability | 16 |
| 7.9 | Surface temperature | 16 |
| 7.10 | Resistance to ignition | 16 |
| 7.11 | Seating adjustments for tilt and recline systems | 17 |
| 7.12 | Castor stem | 17 |
| 7.13 | Electrically powered ancillary equipment | 17 |
| 7.14 | Pushing force | 18 |
| 8 | Requirements for information supplied by the manufacturer | 18 |
| 8.1 | General | 18 |
| 8.2 | Pre-sale information | 19 |
| 8.3 | User information | 19 |
| 8.4 | Service information | 20 |
| 8.5 | Labelling | 20 |
| 9 | Test report | 21 |
| 10 | Tables | 21 |

| | | |
|---|---|----|
| 11 | Figures | 22 |
| A.3 | Accelerometer mounting | 26 |
| A.4 | Design aims | 27 |
| Annex B (informative) Recommendations for dimensions and manoeuvring space | | 35 |
| B.1 | Specific dimensions | 35 |
| B.1.1 | Dimensions when ready for use and when folded and/or dismantled | 35 |
| B.1.2 | Push handle height | 35 |
| B.1.3 | Ground clearance | 35 |
| B.2 | Manoeuvring space | 35 |
| B.2.1 | Turning diameter | 35 |
| B.2.2 | Reversing width | 35 |
| Annex C (informative) Recommended design features | | 37 |
| C.1 | Introduction | 37 |
| C.2 | General recommendations | 37 |
| C.2.1 | Fittings and tools | 37 |
| C.2.2 | Tyres | 37 |
| C.2.3 | Means to inflate tyres | 37 |
| C.2.4 | Surface temperature | 37 |
| C.2.5 | Occupant transfer into or out of the wheelchair | 37 |
| C.2.6 | Resistance to contamination from urine incontinence | 38 |
| C.2.7 | Head support | 38 |
| C.2.8 | Accidental release of parking brakes | 38 |
| C.2.9 | Tipping device | 38 |
| C.2.10 | Anti-tip devices | 38 |
| Annex D (informative) Recommended seating design | | 39 |
| Annex E (informative) Manoeuvring forces | | 40 |
| E.1 | Recommendations | 40 |
| E.1.1 | Push handle force | 40 |
| E.1.2 | Handrim force | 40 |
| F.1 | Technical changes between the first (1999) and second (2006) editions | 41 |
| F.2 | Technical changes from the second (2006) edition | 42 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Council Directive 93/42/EEC of 14 June 1993 concerning medical devices | | 43 |
| Bibliography | | 47 |
| Annex A (informative) Recommendations for test dummies of mass greater than 100 kg | | 26 |
| A.1 | General | 26 |
| A.2 | Construction | 26 |