

ISO 23919:2020-04 (E)

Cigarettes - Determination of ammonia in cigarette mainstream smoke using ion chromatography

| Contents | Page |
|---|-------------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Principle | 1 |
| 5 Apparatus | 2 |
| 6 Reagents | 2 |
| 7 Preparation | 2 |
| 7.1 General | 2 |
| 7.2 Preparation of solutions | 3 |
| 7.2.1 Sulphuric acid, 0,01 M — Impinger solution (trapping system 1) | 3 |
| 7.2.2 Sulphuric acid, 0,1 M — Solution C (Ion chromatography eluent) | 3 |
| 7.2.3 MSA 0,003 M — Solution A (Ion chromatography eluent) | 3 |
| 7.2.4 Sulphuric acid, 0,01 M — Ammonium standards preparation | 3 |
| 7.2.5 Hydrochloric acid, 0,05 M — Solution for glass fibre filter pad impregnation (trapping system 2) | 3 |
| 7.2.6 Hydrochloric acid, 0,01 M — Extraction solution (trapping system 2) | 3 |
| 7.3 Preparation of standards | 3 |
| 7.3.1 Primary ammonium stock solution | 3 |
| 7.3.2 Calibration standards | 3 |
| 8 Sampling | 4 |
| 9 Tobacco product preparation | 4 |
| 10 Sample generation — Smoking of cigarettes | 4 |
| 10.1 General | 4 |
| 10.2 Smoking machine setup | 4 |
| 10.2.1 Trapping system 1 — Glass fibre filter pad and impinger traps | 4 |
| 10.2.2 Trapping system 2 — Impregnated glass fibre filter pad | 5 |
| 10.3 Smoking | 6 |
| 11 Sample analysis | 6 |
| 11.1 Preparation of sample | 6 |
| 11.1.1 Extraction of glass fibre filter pad — Trapping system 1 | 6 |
| 11.1.2 Extraction of glass fibre filter pad — Trapping system 2 | 6 |
| 11.2 Determination | 6 |
| 11.2.1 Ion chromatography operating conditions | 6 |
| 11.2.2 Calibration | 7 |
| 11.2.3 Calculation | 8 |
| 12 Repeatability and reproducibility | 8 |
| 12.1 General | 8 |
| 12.2 Results of the 2015 collaborative study | 9 |
| 13 Report | 9 |
| Annex A (informative) Examples of chromatograms | 10 |
| Bibliography | 11 |