

ISO 10846-2:2008-08 (E)

Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 2: Direct method for determination of the dynamic stiffness of resilient supports for translatory motion

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	2
3	Terms and definitions	3
4	Principle	6
5	Requirements for apparatus	6
5.1	Normal translations	6
5.2	Transverse translations	8
5.3	Suppression of unwanted vibrations	11
6	Criteria for adequacy of the test arrangement	12
6.1	Frequency range	12
6.2	Measurement of blocking force	12
6.3	Flanking transmission	13
6.4	Unwanted input vibrations	13
6.5	Accelerometers	14
6.6	Force transducers	14
6.7	Summation of signals	14
6.8	Analysers	15
7	Test procedures	15
7.1	Installation of the test elements	15
7.2	Selection of force measurement system and output-force distribution plates	15
7.3	Mounting and connection of accelerometers	15
7.4	Mounting and connections of the vibration exciter	16
7.5	Source signal	16
7.6	Measurements	16
7.7	Test for linearity	17
8	Evaluation of test results	18
8.1	Calculation of dynamic transfer stiffness	18
8.2	One-third-octave-band values of the frequency-averaged dynamic transfer stiffness	18
8.3	Presentation of one-third-octave-band results	19
8.4	Presentation of narrow-band data	20
9	Information to be recorded	21
10	Test report	22
Annex A (informative) Static load-deflection curve		23
Annex B (informative) Measurement uncertainty		24
Bibliography		28