

ISO 10846-5:2008-08 (E)

Acoustics and vibration - Laboratory measurement of vibro-acoustic transfer properties of resilient elements - Part 5: Driving point method for determination of the low-frequency transfer stiffness of resilient supports for translatory motion

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	2
3	Terms and definitions	3
4	Principle	5
5	Test arrangements	6
5.1	Normal translations	6
5.2	Transverse translations	7
5.3	Suppression of unwanted vibrations	8
6	Criteria for adequacy of the test arrangement	11
6.1	General requirements	11
6.2	Determination of upper limiting frequency	12
6.3	Force transducers	12
6.4	Accelerometers	12
6.5	Summation of signals	13
6.6	Analysers	13
7	Test procedures	13
7.1	Selection of force measurement system and force distribution plates	13
7.2	Installation of the test element	13
7.3	Mounting and connection of accelerometers	14
7.4	Mounting and connections of the vibration exciter	14
7.5	Source signal	14
7.6	Measurements	14
7.7	Test for linearity	15
8	Evaluation of test results	16
8.1	Calculation of dynamic driving-point stiffness	16
8.2	One-third-octave-band values of the frequency-averaged dynamic driving-point stiffness	17
8.3	One-third-octave-band values of the frequency-averaged transfer stiffness	17
8.4	Presentation of one-third-octave-band results	17
8.5	Presentation of narrow-band data	18
9	Information to be recorded	19
10	Test report	20
Annex A (informative) Static load-deflection curve		21
Annex B (informative) Measurement uncertainty		22
Bibliography		26