

# ISO 16063-1:1998-10 (E)

## Methods for the calibration of vibration and shock transducers - Part 1: Basic concepts

---

| <b>Contents</b>  |   | <b>Page</b> |
|--|---|-------------|
| <b>1</b>   | <b>Scope .....</b>                                    | <b>1</b>    |
| <b>2</b>   | <b>Normative references .....</b>                     | <b>1</b>    |
| <b>3</b>   | <b>Terms and definitions .....</b>                    | <b>1</b>    |
| <b>4</b>   | <b>Characteristics to be measured .....</b>           | <b>4</b>    |
| <b>4.1</b>   | <b>General .....</b>                                  | <b>4</b>    |
| <b>4.2</b>   | <b>Direct response .....</b>                          | <b>4</b>    |
| <b>4.3</b>   | <b>Spurious response .....</b>                        | <b>5</b>    |
| <b>5</b>   | <b>Calibration methods .....</b>                      | <b>7</b>    |
| <b>5.1</b>   | <b>General .....</b>                                  | <b>7</b>    |
| <b>5.2</b>   | <b>Primary calibration methods .....</b>              | <b>8</b>    |
| <b>5.3</b>   | <b>Comparison calibration methods .....</b>           | <b>17</b>   |
| <b>6</b>   | <b>Expression of uncertainty of measurement .....</b> | <b>18</b>   |
| <b>Annex A (informative) Expression of uncertainty of measurement in calibration .....</b> |   | <b>19</b>   |
| <b>Bibliography .....</b>  |   | <b>22</b>   |