ISO/TS 7849-2:2009-03 (E)

Acoustics - Determination of airborne sound power levels emitted by machinery using vibration measurement - Part 2: Engineering method including determination of the adequate radiation factor

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Principle 4

5 Measuring instrumentation 5
5.1 General 5
5.2 Vibration transducer 5
5.3 Non-contacting transducers 6
5.4 Amplifier and filter 6
5.5 Integrator 6
5.6 Calibration 6

6 Installation and operation of source under test 7
6.1 General 7
6.2 Description of the machine 7
6.3 Installation 7
6.4 Operating conditions 7

7 Determination of the vibratory velocity on the vibrating measurement surface 7
7.1 General 7
7.2 Vibrating measurement surface 8
7.3 Number of measurement positions 8
7.4 Environmental conditions 9
7.5 Measurement procedure 9
7.6 Mounting of the vibration transducer 9

8 Determination of the machinery specific frequency band radiation factor 10

9 Calculations 11
9.1 Correction for extraneous vibratory velocity 11
9.2 Determination of the mean vibratory velocity level on the vibrating measurement surface 12
9.3 Calculation of the airborne sound power level caused by radiation of structure vibration generated sound 13

10 Measurement uncertainty 13
11 Information to be recorded 14
11.1 Machine under test 14
11.2 Measurement conditions 15
11.3 Measuring instrumentation 15
11.4 Acoustical data 15

Annex A (informative) Use of the vibration transducer 16

Annex B (normative) Procedures for calculating A-weighted sound power levels from octave band or one-third-octave band levels 18

Annex C (informative) Recommendations concerning the frequency bands of interest 20

Annex D (informative) Determination of the vibratory velocity level from the vibratory acceleration level 21

Annex E (informative) Guidance on the development of information on measurement uncertainty .. 23

Bibliography 26