

DIN ISO 10816-2:2010-06 (E)

Mechanical vibration - Evaluation of machine vibration by measurements on non-rotating parts - Part 2: Land-based steam turbines and generators in excess of 50 MW with normal operating speeds of 1500 r/min, 1800 r/min, 3000 r/min and 3600 r/min (ISO 10816-2:2 009)

| Contents | | Page |
|--|---|-------------|
| National foreword | | 2 |
| National Annex NA (informative) Bibliography | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Measurement procedures | 7 |
| 4 | Evaluation criteria | 8 |
| 4.1 | General | 8 |
| 4.2 | Criterion I: Vibration magnitude | 9 |
| 4.3 | Criterion II: Change in vibration magnitude under steady-state conditions at normal operating speed | 13 |
| 4.4 | Supplementary procedures/criteria | 14 |
| 4.5 | Evaluation based on vibration vector information | 14 |
| Annex A (normative) Evaluation zone boundaries | | 15 |
| Annex B (informative) Example of setting ALARM and TRIP values | | 16 |
| Annex C (informative) Cautionary notes about the use of vibration velocity criteria at low rotational speeds | | 17 |
| Bibliography | | 19 |