

# DIN 45673-5:2010-08 (E)

## Mechanical vibration - Resilient elements used in railway tracks - Part 5: Laboratory test procedures for under-ballast mats

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
1	Scope .....	4
2	Normative references .....	4
3	Overview and general principles .....	5
4	Under-ballast mats for reducing vibrations, structure-borne noise and secondary air-borne noise .....	5
4.1	Static bedding modulus .....	5
4.2	Lower-frequency dynamic bedding modulus $C_{dyn 1}(f)$ for determining track dynamics ....	7
4.3	Lower-frequency dynamic stiffening ratio $dyn 1(10\text{ Hz})$ .....	9
4.4	Higher-frequency dynamic bedding modulus $C_{dyn 2}(f)$ for determining the efficiency of mitigating structure-borne noise .....	9
4.5	Higher-frequency dynamic stiffening ratio $dyn 2(20\text{ Hz})$ .....	10
4.6	Loss factor .....	11
5	Under-ballast mats to reduce ballast stress at high running speeds .....	11
5.1	Static bedding modulus .....	11
5.2	Dynamic bedding modulus for determining track dynamics .....	11
5.3	Lower-frequency dynamic stiffening ratio .....	11
5.4	Horizontal static bedding modulus $C_{stat,h}$ .....	11
6	Fitness for purpose .....	12
6.1	General .....	12
6.2	Mechanical fatigue strength .....	13
6.3	Material identification testing .....	15
6.4	Material and component testing .....	15
7	Quality monitoring, quality assurance .....	18
Bibliography .....		19