

# ISO 18312-2:2012-01 (E)

## Mechanical vibration and shock - Measurement of vibration power flow from machines into connected support structures - Part 2: Indirect method

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b> .....		<b>iv</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Fundamentals</b> .....	<b>4</b>
4.1	General material for determination of emitted vibration power .....	4
4.2	Expression of vibration power in different forms .....	7
<b>5</b>	<b>Measurement</b> .....	<b>8</b>
5.1	Vibration transducers arrangement .....	8
5.2	Typical signal processing for evaluation of acceleration cross-spectrum .....	11
5.3	Metrological specifications .....	11
<b>6</b>	<b>Test procedures</b> .....	<b>12</b>
6.1	Choice of number of vibration isolators to measure from .....	12
6.2	Transducer placement and determination of maximum frequency .....	12
<b>7</b>	<b>Measurement uncertainty</b> .....	<b>13</b>
<b>8</b>	<b>Data presentation and test report</b> .....	<b>13</b>
<b>Annex A (informative) Construction of dynamic stiffness matrix of vibration isolators</b> .....		<b>15</b>
<b>Annex B (informative) Examples of simple geometries and linear components of dynamic stiffness matrix for massless isolators</b> .....		<b>16</b>
<b>Bibliography</b> .....		<b>18</b>