ISO 14839-4:2012-03 (E)

Mechanical vibration - Vibration of rotating machinery equipped with active magnetic bearings - Part 4: Technical guidelines

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Active magnetic bearing system architecture 2

5 Important differences between magnetic bearings and conventional bearings 3
5.1 Some advantages of active magnetic bearings 3
5.2 Some disadvantages of active magnetic bearings 5
5.3 Comparisonamongrolling,fluidfilmandmagneticbearings 6

6 System condition monitoring 6
6.1 General 6
6.2 Excess rotor shaft displacement (radial x, y, and axial z) 6
6.3 Excess of rotor expansion 8
6.4 Overload of bearing (over current of bearing coil) 8
6.5 Bearing temperature high 8
6.6 Overspeed of rotor 8
6.7 Power supply defect 8
6.8 Battery power defect 8
6.9 Controller temperature high 8
6.10 Cooling 9

7 Environmental factors 9
7.1 Introduction 9
7.2 Environmental category tables 10
7.3 Explosive atmosphere types 13

8 System requirements 13
8.1 Estimation of bearing load 13
8.2 Limitation of dl/dt for laminated bearings 14
8.3 Balancing 16
8.4 Location of bearings and transducers 17
8.5 Fault recovery and fault handling 17
8.6 Signal processing 17
8.7 Monitoring system 17

9 Touchdown bearings 18
9.1 Touchdown bearing requirements 18
9.2 Design of touchdown bearings 18
9.3 Touchdown bearing monitoring 20
9.4 Touchdown test methods 20

10 Preventive inspection 22
10.1 Introduction 22
10.2 Regular inspection and maintenance 22
10.3 Condition monitoring (recommendation) 22

10.4 Inspection checklist 23

Annex A (informative) Sizing of magnetic bearings 24

Annex B (informative)Exampleofadesignspecificationchecklist 27

Annex C (informative) Example conditions for acceptance tests 29

Annex D (informative) Touchdown test method example 30

Annex E (informative) Example of system limitations (current/voltage saturation) 32

Annex F (informative) Unbalance control 35

Bibliography 40