ISO 16283-1:2014-02 (E)

Acoustics - Field measurement of sound insulation in buildings and of building elements - Part 1: Airborne sound insulation

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Instrumentation 5
4.1 General 5
4.2 Calibration 5
4.3 Verification 5

5 Frequency range 5

6 General 6

7 Default procedure for sound pressure level measurement 7
7.1 General 7
7.2 Generation of sound field 7
7.3 Fixed microphone positions 8
7.4 Mechanized continuously-moving microphone 9
7.5 Manually-scanned microphone 10
7.6 Minimum distances for microphone positions 12
7.7 Averaging times 12
7.8 Calculation of energy-average sound pressure levels 13

8 Low-frequency procedure for sound pressure level measurement 14
8.1 General 14
8.2 Generation of sound field 14
8.3 Microphone positions 14
8.4 Averaging time 15
8.5 Calculation of low-frequency energy-average sound pressure levels 15

9 Background noise (default and low-frequency procedure) 16
9.1 General 16
9.2 Correction to the signal level for background noise 17

10 Reverberation time in the receiving room (default and low-frequency procedure) 17
10.1 General 17
10.2 Generation of sound field 18
10.3 Default procedure 18
10.4 Low-frequency procedure 18
10.5 Interrupted noise method 18
10.6 Integrated impulse response method 18

11 Conversion to octave bands 19

12 Recording results 19

13 Uncertainty 19

14 Test report 19

Annex A (normative) Requirements for loudspeakers 21

Annex B (informative) Forms for recording results 22

Annex C (informative) Additional guidance 25

Annex D (informative) Horizontal measurements -- Examples of suitable loudspeaker and microphone positions 30

Annex E (informative) Vertical measurements -- Examples of suitable loudspeaker and microphone positions 37

Bibliography 43