

ISO/TR 17534-3:2015-01 (E)

Acoustics - Software for the calculation of sound outdoors - Part 3: Recommendations for quality assured implementation of ISO 9613-2 in software according to ISO 17534-1

| Contents | Page |
|---|----------|
| Foreword..... | v |
| Introduction..... | vi |
| 1 Scope..... | 1 |
| 2 Normative references..... | 1 |
| 3 Terms and definitions..... | 1 |
| 4 Identification of the official documentation..... | 1 |
| 5 Additional recommendations..... | 1 |
| 5.1 General..... | 1 |
| 5.2 Screening..... | 2 |
| 5.3 Limitation of the maximal possible attenuation by barriers..... | 4 |
| 5.4 Calculation of the path-length difference, z | 4 |
| 5.5 Diffraction with barrier on reflecting ground..... | 4 |
| 5.6 No level increase caused by barriers due to lateral diffraction..... | 4 |
| 5.7 No ground effect calculated with rays laterally diffracted..... | 5 |
| 5.8 No lateral diffraction with elevated ground screening the direct ray..... | 5 |
| 5.9 Multi-reflection..... | |
| the extension to reflections of higher orders..... | 5 |
| 6 Test cases..... | 6 |
| 6.1 General..... | 6 |
| 6.2 Test cases with step by step results and final result interval..... | 6 |
| 6.2.1 T01-T03..... | |
| Flat ground with homogeneous acoustic properties..... | 6 |
| 6.2.2 T01..... | |
| Reflecting ground ($G = 0$)..... | 7 |
| 6.2.3 T02..... | |
| Mixed ground ($G = 0,5$)..... | 8 |
| 6.2.4 T03..... | |
| Porous ground ($G = 1$)..... | 9 |
| 6.2.5 T04..... | |
| Flat ground with spatially varying acoustic properties..... | 9 |
| 6.2.6 T05..... | |
| Identical to T04, but calculation with the alternative method according to ISO 9613-2:1996, 7.3.2..... | 11 |
| 6.2.7 T06..... | |
| Ground with spatially varying heights and acoustic properties..... | 12 |
| 6.2.8 T07..... | |
| Identical to T06, but calculation with the alternative method according to ISO 9613-2:1996, 7.3.2..... | 15 |
| 6.2.9 T08..... | |
| Flat ground with spatially varying acoustic properties and long barrier..... | 16 |
| 6.2.10 T09..... | |
| Flat ground with spatially varying acoustic properties and short barrier..... | 19 |
| 6.2.11 T10..... | |
| Ground with spatially varying heights and acoustic properties and short barrier..... | 22 |

| | | | |
|----------|--|--|-----------|
| 6.2.12 | T11 | Flat ground with homogeneous acoustic properties and cubic building receiver at low height | 24 |
| 6.2.13 | T12 | Flat ground with homogeneous acoustic properties and cubic building receiver at large height | 28 |
| 6.2.14 | T13 | Flat ground with homogeneous acoustic properties and polygonal building receiver at low height | 31 |
| 6.2.15 | T14 | Ground with spatially varying heights and acoustic properties and polygonal building | 34 |
| 6.2.16 | T15 | Flat ground with homogeneous acoustic properties and polygonal building receiver at large height | 37 |
| 6.2.17 | T16 | Flat ground with homogeneous acoustic properties and three buildings | 39 |
| 6.2.18 | T17 | Flat ground with homogeneous acoustic properties and three buildings ... alternative position of source and receiver | 43 |
| 6.2.19 | T18 | Flat ground with homogeneous acoustic properties and complex building with backyard | 46 |
| 6.2.20 | T19 | Ground with spatially varying heights and acoustic properties and reflecting barrier | 50 |
| 7 | Declaration of conformity (DOC) | | 52 |
| | Bibliography | | 56 |