

ISO/TR 17534-3:2015-01 (E)

Acoustics - Software for the calculation of sound outdoors - Part 3: Recommendations for quality assured implementation of ISO 9613-2 in software according to ISO 17534-1

Contents	Page
Foreword.....	v
Introduction.....	vi
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Identification of the official documentation.....	1
5 Additional recommendations.....	1
5.1 General.....	1
5.2 Screening.....	2
5.3 Limitation of the maximal possible attenuation by barriers.....	4
5.4 Calculation of the path-length difference, z	4
5.5 Diffraction with barrier on reflecting ground.....	4
5.6 No level increase caused by barriers due to lateral diffraction.....	4
5.7 No ground effect calculated with rays laterally diffracted.....	5
5.8 No lateral diffraction with elevated ground screening the direct ray.....	5
5.9 Multi-reflection.....	
the extension to reflections of higher orders.....	5
6 Test cases.....	6
6.1 General.....	6
6.2 Test cases with step by step results and final result interval.....	6
6.2.1 T01-T03.....	
Flat ground with homogeneous acoustic properties.....	6
6.2.2 T01.....	
Reflecting ground ($G = 0$).....	7
6.2.3 T02.....	
Mixed ground ($G = 0,5$).....	8
6.2.4 T03.....	
Porous ground ($G = 1$).....	9
6.2.5 T04.....	
Flat ground with spatially varying acoustic properties.....	9
6.2.6 T05.....	
Identical to T04, but calculation with the alternative method according to ISO 9613-2:1996, 7.3.2.....	11
6.2.7 T06.....	
Ground with spatially varying heights and acoustic properties.....	12
6.2.8 T07.....	
Identical to T06, but calculation with the alternative method according to ISO 9613-2:1996, 7.3.2.....	15
6.2.9 T08.....	
Flat ground with spatially varying acoustic properties and long barrier.....	16
6.2.10 T09.....	
Flat ground with spatially varying acoustic properties and short barrier.....	19
6.2.11 T10.....	
Ground with spatially varying heights and acoustic properties and short barrier.....	22

6.2.12	T11	Flat ground with homogeneous acoustic properties and cubic building receiver at low height	24
6.2.13	T12	Flat ground with homogeneous acoustic properties and cubic building receiver at large height	28
6.2.14	T13	Flat ground with homogeneous acoustic properties and polygonal building receiver at low height	31
6.2.15	T14	Ground with spatially varying heights and acoustic properties and polygonal building	34
6.2.16	T15	Flat ground with homogeneous acoustic properties and polygonal building receiver at large height	37
6.2.17	T16	Flat ground with homogeneous acoustic properties and three buildings	39
6.2.18	T17	Flat ground with homogeneous acoustic properties and three buildings ... alternative position of source and receiver	43
6.2.19	T18	Flat ground with homogeneous acoustic properties and complex building with backyard	46
6.2.20	T19	Ground with spatially varying heights and acoustic properties and reflecting barrier	50
7	Declaration of conformity (DOC)		52
	Bibliography		56