

# ISO 16063-17:2016-06 (E)

## Methods for the calibration of vibration and shock transducers - Part 17: Primary calibration by centrifuge

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Requirements for apparatus and environmental conditions .....</b>	<b>1</b>
4.1	Calibration environment .....	1
4.2	Balanced table or arm (rotational table) .....	1
4.3	Rotational frequency measuring instrumentation .....	2
4.4	Voltage-measuring instrumentation .....	3
<b>5</b>	<b>Preferred values .....</b>	<b>3</b>
<b>6</b>	<b>Method 1 (with measurement of the radius of rotation) .....</b>	<b>3</b>
6.1	Test procedure .....	3
6.2	Expression of results .....	3
<b>7</b>	<b>Method 2 (without measurement of the radius of rotation) .....</b>	<b>4</b>
7.1	Test procedure .....	4
7.2	Expression of results .....	4
<b>Annex A (informative) Expression of uncertainty of measurement in calibration .....</b>		<b>5</b>
<b>Bibliography .....</b>		<b>7</b>