

ISO 362-3:2016-07 (E)

Measurement of noise emitted by accelerating road vehicles - Engineering method - Part 3: Indoor testing M and N categories

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Symbols and abbreviated terms | 2 |
| 5 | Acceleration for vehicles of categories M1 and M2 having a maximum authorized mass not exceeding 3 500 kg, and of category N1 | 5 |
| 5.1 | General | 5 |
| 5.1.1 | Applicability and conditions | 5 |
| 5.1.2 | Calculation of total engine power | 5 |
| 5.1.3 | Battery state of charge | 5 |
| 5.2 | Calculation of acceleration | 5 |
| 5.2.1 | Calculation procedure for vehicles with manual transmission, automatic transmission, adaptive transmission, and continuously variable transmission (CVT) tested with locked gear ratios | 5 |
| 5.2.2 | Calculation procedure for vehicles with automatic transmission, adaptive transmission, and CVT tested with non-locked gear ratios | 5 |
| 5.3 | Calculation of the target acceleration | 6 |
| 5.4 | Calculation of the reference acceleration | 6 |
| 5.5 | Partial power factor, kP | 6 |
| 6 | Instrumentation | 6 |
| 6.1 | Instruments for acoustical measurement | 6 |
| 6.1.1 | General | 6 |
| 6.1.2 | Calibration | 7 |
| 6.2 | Conformity with requirements | 7 |
| 6.3 | Instrumentation for speed measurement | 7 |
| 6.4 | Meteorological instrumentation | 7 |
| 7 | Test room requirements | 7 |
| 7.1 | General | 7 |
| 7.2 | Test room dimensions | 8 |
| 7.3 | Acoustical qualification of the room | 10 |
| 7.3.1 | General | 10 |
| 7.3.2 | Validation of free-field conditions | 10 |
| 7.3.3 | Qualification procedure | 13 |
| 7.4 | Condition of the floor | 14 |
| 7.5 | Cooling, ventilation, air temperature, exhaust gas management | 14 |
| 7.6 | Background noise | 14 |
| 8 | Dynamometer requirements | 15 |
| 8.1 | Type of texture of the rollers | 15 |
| 8.2 | Diameter of the rollers | 15 |
| 8.3 | Reproducibility of the pass-by dynamics | 15 |

| | | |
|--------|---|----|
| 8.4 | Single-axle or multi-axle operation | 16 |
| 8.5 | Noise emission limit under operating conditions produced by the dynamometer rollers | 16 |
| | 9 Test procedures | 16 |
| 9.1 | General | 16 |
| 9.2 | Microphone array -- Hardware and software | 16 |
| 9.3 | Vehicle fixing system | 17 |
| 9.4 | Conditions of the vehicle | 17 |
| 9.4.1 | General conditions | 17 |
| 9.4.2 | Test mass of the vehicle | 17 |
| 9.4.3 | Tyre selection and tyre condition | 18 |
| 9.5 | Operating conditions | 19 |
| 9.5.1 | Vehicles of categories M1, M2 having a maximum authorized mass not exceeding 3 500 kg, and N1 | 19 |
| 9.5.2 | Vehicles of categories M2 having a maximum authorized mass exceeding 3 500 kg, M3, N2 and N3 | 19 |
| 9.6 | Measurement readings and reported values | 20 |
| 9.6.1 | General | 20 |
| 9.6.2 | Data compilation | 21 |
| 9.6.3 | Vehicles of categories M1 and M2 having a maximum authorized mass not exceeding 3 500 kg, and of category N1 | 21 |
| 9.6.4 | Vehicles of categories M2 having a maximum authorized mass exceeding 3 500 kg, M3, N2, and N3 | 21 |
| 9.7 | Measurement uncertainty | 21 |
| 10 | Test methods and test report | 22 |
| 10.1 | General | 22 |
| 10.2 | Variant A | 22 |
| 10.2.1 | General | 22 |
| 10.2.2 | Power train noise | 22 |
| 10.2.3 | Tyre/road noise | 22 |
| 10.2.4 | Calculation of the total vehicle noise using variant A | 23 |
| 10.3 | Test report | 23 |
| | Annex A (normative) Validation of method | 24 |
| | Annex B (normative) Procedure for measurement, evaluation, and calculation of tyre/road noise when using variant A | 28 |
| | Annex C (informative) Procedure for measurement, evaluation, and calculation of tyre/ road noise when using variant B | 41 |
| | Annex D (informative) Measurement uncertainty -- Framework for analysis according to ISO/IEC Guide 98-3 | 43 |
| | Annex E (informative) Room length deviation from recommendation | 49 |
| | Bibliography | 51 |