

ISO 10848-1:2017-09 (E)

Acoustics - Laboratory and field measurement of flanking transmission for airborne, impact and building service equipment sound between adjoining rooms - Part 1: Frame document

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Quantities to characterize flanking transmission | 7 |
| 4.1 | General | 7 |
| 4.2 | Normalized flanking level difference, $D_{n,f}$, normalized flanking impact sound pressure level, $L_{n,f}$, and normalized flanking equipment sound pressure level, $L_{ne0,f}$ | 8 |
| 4.2.1 | General | 8 |
| 4.2.2 | $D_{v,ij,n}$ estimated from measurements of $D_{n,f}$ | 8 |
| 4.3 | Vibration reduction index, K_{ij} | 8 |
| 4.3.1 | General | 8 |
| 4.3.2 | K_{ij} for combinations of Type A and B elements | 9 |
| 4.3.3 | Strong coupling between Type A elements | 9 |
| 4.4 | Normalized direction-average vibration level difference, $D_{ijv, ,n}$ | 9 |
| 4.4.1 | General | 9 |
| 4.5 | Selection of the measurement method | 10 |
| 5 | Instrumentation | 10 |
| 5.1 | General | 10 |
| 5.2 | Verification | 11 |
| 6 | General requirements for test facility and test elements | 11 |
| 6.1 | Laboratory | 11 |
| 6.2 | Field | 14 |
| 7 | Measurement methods | 14 |
| 7.1 | Measurement of $D_{n,f}$, $L_{n,f}$ and $L_{ne0,f}$ | 14 |
| 7.1.1 | Generation of sound field in the source room | 14 |
| 7.1.2 | Measurement of the average sound pressure level | 16 |
| 7.1.3 | Measurement of reverberation time and evaluation of the equivalent sound absorption area | 18 |
| 7.2 | Measurement of K_{ij} and $D_{v, ,nij}$ | 18 |
| 18 | 7.2.1 General aspects for K_{ij} | 18 |
| 7.2.2 | General aspects for $D_{v, ,nij}$ | 18 |
| 18 | 7.2.3 Vibration measurement | 19 |
| 7.2.4 | Generation of vibration on the source element | 20 |
| 7.2.5 | Procedure for Type A and B elements | 20 |
| 7.2.6 | Steady-state excitation | 21 |
| 7.2.7 | Transient excitation | 22 |
| 7.3 | Measurement of the structural reverberation time for Type A elements | 22 |

| | | |
|---|---|----|
| 7.3.1 | General | 22 |
| 7.3.2 | Excitation of the test element | 22 |
| 7.3.3 | Measurement and excitation positions | 23 |
| 7.3.4 | Evaluation of the decay curves | 23 |
| 7.3.5 | Lower limits for reliable results caused by filter and detector | 24 |
| 7.4 | Frequency range of measurement | 24 |
| 8 | Influences from other parts of the test facility or the building construction in the field situation | 24 |
| 8.1 | Laboratory installations of test junctions | 24 |
| 8.2 | Criterion to assess flanking transmission for junctions comprised of Type A elements | 25 |
| 8.2.1 | General | 25 |
| 8.2.2 | Practical considerations | 25 |
| 8.3 | Verification procedure for a Type B flanking element that is structurally independent of a separating element | 25 |
| 9 | Shielding | 26 |
| 10 | Expression of results | 26 |
| Annex A (normative) Assessing the decrease in vibration level with distance | | 28 |
| Annex B (normative) Calibrated structure-borne sound source | | 30 |
| Bibliography | | 34 |