

ISO 20816-5:2018 (E)

Mechanical vibration — Measurement and evaluation of machine vibration — Part 5: Machine sets in hydraulic power generating and pump-storage plants

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Machine arrangements |
| 5 | Measurement procedures and conditions |
| 5.1 | General |
| 5.1.1 | Bearing housing vibration measurements |
| 5.1.2 | Shaft vibration measurements |
| 5.2 | Measurement types |
| 5.2.1 | Absolute bearing housing vibration |
| 5.2.2 | Radial shaft vibration |
| 5.2.2.1 | General |
| 5.2.2.2 | Relative shaft vibration measurements |
| 5.2.2.3 | Absolute shaft vibration measurements |
| 5.2.3 | Bearing and shaft vibration in the axial direction |
| 5.2.4 | Detrimental influences |
| 5.3 | Measurement locations and directions |
| 5.3.1 | General |
| 5.3.2 | Measurement of relative shaft vibration |
| 5.3.3 | Measurement of the absolute bearing housing vibration |
| 5.4 | Measurement equipment |
| 5.4.1 | General |
| 5.4.2 | Absolute bearing housing vibration measurements |
| 5.4.3 | Shaft vibration measurement |
| 5.4.4 | Measurement of S_{max} or S_{p-p} |
| 5.5 | Operational conditions |
| 6 | Evaluation of vibration measurements |
| 6.1 | General |
| 6.1.1 | Basis of the vibration values |
| 6.1.2 | Effect of turbine operating conditions on bearing housing vibration measurements |
| 6.1.3 | Effect of turbine operating conditions on shaft vibration |
| 6.1.4 | Pump operating conditions |
| 6.1.5 | Special operating conditions |
| 6.2 | Criterion I: Vibration magnitude |
| 6.3 | Criterion II: Change in vibration magnitude and phase |
| 6.3.1 | Assessment criteria |
| 6.3.2 | Monitoring prerequisites |
| 6.3.3 | Specific recommendation related to the generator |
| 6.4 | Operational limits |
| 6.4.1 | Alarms and trips |
| 6.4.2 | Setting of alarms |
| 6.4.3 | Setting of trips |
| 6.4.4 | Special operating conditions |
| 6.5 | Comparison of results for shaft vibration and bearing housing vibration |

- 6.6 Evaluation based on vibration vector information**
- Annex A (normative) Evaluation zone boundaries**
 - A.1 Vibration action limits**
 - A.2 Application of the specified limit values and actions**
 - A.3 Actions to be taken when the action limits are exceeded**
 - A.3.1 Action limit 1**
 - A.3.2 Action limit 2**
 - A.4 Examples of measured vibration values**
- Annex B (informative) Vibration monitoring — Prerequisite for trend analysis**
 - B.1 General information and recommendation**
 - B.2 Basic physical principle for bearing vibration**
- Annex C (informative) Special features of bearing housing vibration and shaft vibration of hydraulic machine sets**
 - C.1 General**
 - C.2 Frequencies of vibration from mechanical and electrical source**
 - C.3 Mechanical causes**
 - C.4 Electrical causes**
 - C.5 Hydraulic causes**
 - C.5.1 Significant frequencies in the water flow through the water passages**
 - C.5.2 Draft tube flow instabilities**
 - C.5.3 Cavitation**
 - C.5.4 Self-excited vibration**
 - C.5.5 Hydraulically excited vibration**
 - C.6 Additional excitations**
- Annex D (informative) Database, analysis procedure and statistical evaluation**
 - D.1 Collection of measured shaft and bearing housing vibration values**
 - D.2 Statistical evaluation**
- Annex E (informative) Recommended practice for vibration data processing**
 - E.1 General**
 - E.2 Possible data filtering in the time domain**
 - E.3 Possible data filtering in the frequency domain**
 - E.4 Details of the peak-to-peak evaluation**
 - E.4.1 Evaluation procedure**
 - E.4.2 Major findings**
 - E.4.2.1 General**
 - E.4.2.2 Standard deviation based evaluation**
 - E.4.2.3 (Mean) peak-to-peak value of subsets**
 - E.4.2.4 Percentile**