ISO 13473-1:2019 (E)

Characterization of pavement texture by use of surface profiles — Part 1: Determination of mean profile depth

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions

4 Test surfaces

- 4.1 Condition of the surface
- 4.2 Amount of data to be collected per field test section
- 4.2.1 Continuous measurements
- 4.2.2 Spot measurements
- 4.3 Amount of data to be collected on laboratory samples
- 5 Measurement instruments
 - 5.1 Instruments in general
 - 5.2 Vertical resolution
 - 5.3 Horizontal resolution
 - 5.4 Measurement speed
 - 5.5 Alignment of sensor
 - 5.6 Bandwidth of sensor and recording system
 - 5.7 Performance check
 - 5.8 Indication of invalid readings (drop-outs)
 - 5.9 Sensitivity to vibrations
- 6 Measurement procedure
 - 6.1 Performance checks
 - 6.2 Measurements
 - 6.3 Continuous or spot measurements
- 7 Data processing procedure
 - 7.1 General
 - 7.2 Summary of data processing steps
 - 7.3 Drop-out correction and interpolation
 - 7.4 Resampling to a certain spatial resolution
 - 7.5 Spike identification and reshaping the profile
 - 7.6 Removal of long-wavelength components and normalization of profile sharpness
 - 7.7 Segment limiting
 - 7.8 Peak and MSD determination
 - 7.9 Extreme MSD value removal (optional)
 - 7.10 Averaging of MSD to determine the MPD
 - 7.11 Calculation of ETD (optional)
- 8 Measurement uncertainty assessment according to ISO/IEC Guide 98-3
- 9 Safety considerations
- 10 Test report
- Annex A (informative) Texture ranges

Annex B (informative) Problems experienced on special surfaces

- B.1 Porous surfaces
- B.2 Newly laid surfaces and humid/wet surfaces
- B.3 Surfaces with directional finish (e.g. grooved, ground or tined concrete)

Annex C (informative) Procedure for sampling of mean segment depth values by spot measurements

- C.1 Background
- C.2 Procedure
- C.2.1 General
- C.2.2 Case 1: Lane length L is shorter than 1 000 m (L \leq 1 000 m)
- C.2.3 Case 2: Lane length L is longer than 1 000 m (L > 1 000 m)
- C.2.4 Example illustrating Case 2

Annex D (normative) Data quality-enhancing procedures

- D.1 General
- D.2 Summary of the specified data processing procedures
- D.3 Brief description of the procedures
- D.3.1 Drop-out identification (mandatory)
- D.3.2 Maximum use of data (mandatory where applicable)
- D.3.3 Spike identification (mandatory)
- D.3.4 Reshape profile (space domain, mandatory)
- D.3.5 Removal of slope and long-wavelength components (mandatory)
- D.3.6 Normalization of sharpness by low-pass filtering (space domain, mandatory)
- D.3.7 Extreme MSD value removal (space domain, optional, only for MSD determination)
- D.4 Aid in designing the filters

Annex E (normative) Spike removal procedure

- E.1 General
- E.2 Example
- Annex F (informative) Measurement uncertainty
 - F.1 General
 - F.2 Expression for the calculation of the MPD value
 - F.3 Sources of uncertainty
 - F.4 Estimation of uncertainties of the method
- Annex G (informative) Performance check
- Annex H (informative) Flow charts for determination of MSD and MPD

Page count: 43