## ISO 5982:2019 (E)

## Mechanical vibration and shock — Range of idealized values to characterize human biodynamic response under whole-body vibration

## Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Definition of values of apparent mass of the human body under vibration
  - 4.1 Apparent mass of the seated body under x-axis vibration
  - 4.2 Applicability of values of apparent mass of the seated body under x-axis vibration
  - 4.3 Apparent mass of the seated body under y-axis vibration
  - 4.4 Applicability of values of apparent mass of the seated body under y-axis vibration
  - 4.5 Apparent mass of the seated body under z-axis vibration
  - 4.6 Applicability of values of apparent mass of the seated body under z-axis vibration
  - 4.7 Apparent mass of the standing body under z-axis vibration
  - 4.8 Applicability of values of apparent mass of the standing body under z-axis vibration
- 5 Seat-to-head transmissibility of the seated human body under vertical vibration
  - 5.1 Definition of values of seat-to-head transmissibility
  - 5.2 Applicability of values of seat-to-head transmissibility
- Annex A (informative) Identification of the data used to define the range of idealized apparent mass and seat-to-head transmissibility
- Annex B (informative) Lumped mass model
- Annex C (informative) Mathematical models
- Annex D (informative) Apparent mass of seated body under vertical vibration for three different ranges of body masses (55 kg, 75 kg and 98 kg)

Page count: 44