

ISO 7626-5:2019-12 (E)

Mechanical vibration and shock - Experimental determination of mechanical mobility - Part 5: Measurements using impact excitation with an exciter which is not attached to the structure

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	General characteristics of impact measurements	2
4.1	General description	2
4.2	Advantages and limitations of impact excitation	3
4.2.1	General	3
4.2.2	Nonlinearity restrictions	4
4.2.3	Signal-to-noise problems	4
4.2.4	Limited frequency resolution	4
4.2.5	Damping restrictions	4
4.2.6	Dependence on operator skill	5
5	Support of the structure under test	5
5.1	General	5
5.2	Ungrounded measurements	5
5.3	Grounded measurements	5
6	Application of the excitation	5
6.1	Impactor design	5
6.2	Force spectrum characteristics	6
6.3	Control of the frequency range of excitation	10
6.4	Avoidance of impactor double hits	10
7	Transducer system	12
7.1	General	12
7.2	Impactor calibration	12
8	Processing of the transducer signals	13
8.1	Filtering	13
8.2	Transient capture characteristics	13
8.3	Sampling relationships	14
8.4	Avoidance of saturation (clipping)	15
8.5	Windowing techniques	15
8.5.1	Force signal	15
8.5.2	Windowing the response signals	19
8.6	Averaging techniques	23
9	Tests for validity of the measurements	24
9.1	Coherence function	24
9.2	Repeatability check	25
9.3	Reciprocity check	25
9.4	Linearity check	25
9.5	Comparison with measurements using an attached exciter	25
Annex A (informative)	Correction of mobility measurements for the effects of exponential windowing	26
Bibliography		28