ISO 7626-5:2019-12 (E)

Mechanical vibration and shock - Experimental determination of mechanical mobility - Part 5: Measurements using i mpact excitation with an exciter which is not attached to the structure

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 General characteristics of impact measurements 2
4.1 General description 2
4.2 Advantages and limitations of impact excitation 3
4.2.1 General 3
4.2.2 Nonlinearity restrictions 4
4.2.3 Signal-to-noise problems 4
4.2.4 Limited frequency resolution 4
4.2.5 Damping restrictions 4
4.2.6 Dependence on operator skill 5

5 Support of the structure under test 5
5.1 General 5
5.2 Ungrounded measurements 5
5.3 Grounded measurements 5

6 Application of the excitation 5
6.1 Impactor design 5
6.2 Force spectrum characteristics 6
6.3 Control of the frequency range of excitation 10
6.4 Avoidance of impactor double hits 10

7 Transducer system 12
7.1 General 12
7.2 Impactor calibration 12

8 Processing of the transducer signals 13
8.1 Filtering 13
8.2 Transient capture characteristics 13
8.3 Sampling relationships 14
8.4 Avoidance of saturation (clipping) 15
8.5 Windowing techniques 15
8.5.1 Force signal 15
8.5.2 Windowing the response signals 19
8.6 Averaging techniques 23

9 Tests for validity of the measurements 24
9.1 Coherence function 24
9.2 Repeatability check 25
9.3 Reciprocity check 25
9.4 Linearity check 25
9.5 Comparison with measurements using an attached exciter 25

Annex A (informative) Correction of mobility measurements for the effects of exponential windowing 26

Bibliography 28