ISO 14830-1:2019-12 (E)

Condition monitoring and diagnostics of machine systems - Trib ology-based monitoring and diagnostics - Part 1: General requirements and guidel ines

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols (and abbreviated terms) 2

5 Lubricant and wear particle analysis 2
5.1 Asset management 2
5.2 Strategies 2
5.2.1 Before failure onset (as a proactive strategy tool) 2
5.2.2 During failure development (as a predictive strategy tool) 2
5.2.3 Following machine failure (as a reactive strategy tool) 2
5.2.4 Other benefits 2
5.3 Information to be gained through lubricant and wear debris 3
5.3.1 Lubricant properties 3
5.3.2 Lubricant contamination 3
5.3.3 Machine wear 3

6 Measurement parameters 3
6.1 Lubricant and wear debris parameters 3
6.2 Lubricant test suites 3
6.3 Sampling frequency 4

7 Sampling 4
7.1 Objectives 4
7.2 Pressurized sample points 5
7.3 Static sample points 6
7.4 On-line and in-line sampling 7
7.5 Magnetic plug sampling 7
7.6 Grease sampling 8

8 Fluid sampling equipment 8
8.1 General 8
8.2 Sample containers 8
8.3 Sample tubing 8
8.4 Manually operated hand held sample pumps 8
8.5 Other equipment 9
8.6 Sample transport 9

9 Sample analysis 9
9.1 General 9
9.2 On-site analysis 9
9.3 Off-site analysis 10
9.4 Sample documentation 10

10 Alarm criteria 10

11 Diagnosis and prognosis 11

12 Results reporting 12

13 Personnelqualifications 12
13.1 Field analysts 12
13.2 Laboratory analysts 12

Annex A (informative) Common lubricant and wear debris parameters 13

Annex B (informative) Typical lubricant test suites and frequencies 22

Annex C (informative) Sampling procedure examples 25

Annex D (informative) Commercial laboratory selection guidelines 29

Annex E (informative) Sample documentation requirements 31

Annex F (informative) Alarm criteria guidelines 33

Annex G (informative) Diagnosis and prognosis guidelines 38

Bibliography 48