ISO 16079-2:2020 (E)

Condition monitoring and diagnostics of wind turbines — Part 2: Monitoring the drivetrain

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Abbreviated terms

5 Failure mode and symptoms analysis (FMSA)

5.1 General
5.2 The process of the FMSA analysis

6 Descriptors for fault detection

6.1 General
6.2 Descriptor types
6.3 Descriptors based on process parameters — Operational values
6.3.1 General
6.3.2 Measurement of process parameter descriptors
6.4 Measurement of rotational speed and descriptors based on rotational speed
6.4.1 General
6.4.2 Measurement of rotational speed
6.5 Descriptors based on vibration
6.5.1 References to other standards
6.5.2 General
6.5.3 Measurement of vibration
6.5.4 Transducers for vibration measurements
6.5.4.1 IEPE type accelerometers
6.5.4.2 MEMS based accelerometers
6.5.5 Vibration transducer mounting
6.6 Descriptors based on stress wave measurements
6.6.1 General
6.6.2 Measurement of stress waves
6.6.3 Transducers for stress wave measurement
6.6.4 Mounting of stress wave sensors
6.7 Descriptors based on oil debris in lubricant oil
6.7.1 General
6.7.2 Oil debris descriptors
6.7.3 Oil debris sensors

7 Descriptor monitoring interval

7.1 Reference to other standards
7.2 Factors influencing the monitoring interval

8 Descriptor notification criteria

8.1 Reference to other standards
8.2 General
8.3 Establishing descriptor alarm and alert limits for a new turbine
8.4 Establishing alarm and alert limits for a turbine in normal operating condition
8.5 Establishing alert limits upon component change

9 Handling changes in operating conditions — The operational state bin concept

9.1 General
9.2 Example of how to use active power as an operational state

10 Transducer locations

10.1 Reference to other standards and guidelines
10.2 Location of vibration transducers
10.3 Location of stress wave transducers
10.4 Location of oil debris sensors
10.5 Example of naming conventions and transducer locations

11 Baseline — Initial recording of data for diagnosis at commissioning time

11.1 General
11.2 Duration of time waveforms for baseline recording
11.3 Repeatability and stability of time waveform recordings
11.4 Sampling rate of time waveform for baseline recording
11.5 Initial check of the baseline data — Recommendations

12 Diagnosis of faults and their causes

12.1 Reference to other standards
12.2 General
12.3 Component data
12.4 Raw-data time waveforms for detailed diagnosis
12.5 Regular recording
12.6 Recording on request

13 Prognosis

13.1 Reference to other standards
13.2 General
13.3 Type I — Failure data-based prognostics — Statistically based
13.4 Type II — Stress based prognostics — Model based
13.5 Type III — Data-driven method — Condition based

14 Review of the condition monitoring and diagnosis system design

14.1 Reference to other standards
14.2 General
14.3 Assessment of effectiveness of the condition monitoring system
14.4 Cost benefit analysis
14.4.1 General
14.4.2 Simple model
14.4.3 Advanced model

Annex A (informative) Details on vibration-based descriptor types

A.1 Time-domain-based descriptors
A.2 Frequency domain-based narrowband descriptors
A.2.1 General
A.2.2 Frequency domain-based-descriptors generated by feature extraction
A.3 Pre-processing of time waveforms prior to frequency analysis
A.3.1 General
A.3.2 Angular resampling of the time waveform
A.3.3 Time domain averaging
A.4 Feature extraction based on other analysis methods
A.4.1 General
A.4.2 Demodulation — Envelope technique
A.4.3 Cepstrum analysis
A.5 Descriptor measurement time

Annex B (informative) FMSA analysis of the drivetrain

Page count: 45