## ISO 8041-2:2021 (E)

# Human response to vibration — Measuring instrumentation — Part 2: Personal vibration exposure meters

### Contents

Foreword

#### Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Reference environmental conditions
- 5 Performance specifications
  - 5.1 General characteristics
  - 5.1.1 Common characteristics
  - 5.1.2 Special characteristics for whole-body vibration measurement
  - 5.1.3 Special characteristics for hand-arm vibration measurement
  - 5.2 Display
  - 5.3 Electrical output
  - 5.4 Vibration sensitivity
  - 5.5 Accuracy of indication at reference frequency under reference conditions
  - 5.6 Frequency weightings and frequency responses
  - 5.6.1 Parameters
  - 5.6.2 Band-limiting filter
  - 5.6.3 a-v transition filter
  - 5.6.4 Upward-step filter
  - 5.6.5 Overall frequency weighting
  - 5.6.6 Tolerances
  - 5.7 Amplitude linearity
  - 5.8 Instrument noise
  - 5.9 Signal#burst response
  - 5.10 Overload indication
  - 5.11 Under#range indication
  - 5.12 Time averaging
  - 5.13 Running RMS acceleration
  - 5.14 Clearance of data and instrument state (named reset)
  - 5.15 Timing facilities
  - 5.16 Electrical cross-talk
  - 5.17 Vibration transducer characteristics
  - 5.18 Power supply
  - 5.19 Operator detection system
  - 5.20 Detection of transient acceleration artefacts
  - 5.21 Logging capabilities
  - 5.22 Contact force measurement
  - 5.23 Warning indication
  - 5.23.1 General
  - 5.23.2 Mandatory warning indications
  - 5.23.3 Optional warning indications
  - 5.24 Human interface and ergonomic aspects

#### 6 Mounting

7 Environmental and electromagnetic criteria

- 7.1 General
- 7.2 Air temperature
- 7.3 Surface temperature
- 7.4 Electrostatic discharge
- 7.5 Radio-frequency emissions and public-power-supply disturbances
- 7.6 Immunity to AC power-frequency fields and radio-frequency fields
- 7.7 Ingress of water and dust
- 8 Provision for use with auxiliary devices
- 9 Instrument marking
- 10 Instrument documentation
- 11 Performance testing

#### 12 Pattern evaluation

- 12.1 General
- 12.2 Testing requirements
- 12.3 Submission for testing
- 12.4 Marking of the instrument and information in the instrument documentation
- 12.5 Mandatory facilities and general requirements
- 12.6 Initial instrument preparation
- 12.7 Indication at the reference frequency under reference conditions
- 12.8 Electrical cross-talk
- 12.9 Vibration transducer
- 12.10 Amplitude linearity
- 12.10.1 Electrical tests of amplitude linearity
- 12.10.2 Mechanical tests of amplitude linearity
- 12.11 Frequency weightings and frequency responses
- 12.11.1 General
- 12.11.2 Mechanical tests of frequency response
- 12.11.3 Electrical tests of frequency response
- 12.11.4 Conformance
- 12.12 Instrument noise
- 12.13 Signal-burst response
- 12.14 Overload indication
- 12.15 Reset
- 12.16 Combined axis outputs
- 12.17 AC electrical output
- 12.18 Timing facilities
- 12.19 Power supply
- 12.20 Environmental, electrostatic and radio-frequency tests
- 12.20.1 General
- 12.20.2 Expanded uncertainties for measurements of environmental conditions
- 12.20.3 Acclimatization requirements for tests of the influence of air temperature and relative humidity
- 12.20.4 Test of the influence of air temperature and relative humidity combined
- 12.20.5 Influence of surface temperature
- 12.20.6 Influence of electrostatic discharges
- 12.20.7 Radio-frequency emissions and public-power-supply disturbances
- 12.20.8 Immunity to AC power-frequency fields and radio-frequency fields
- 12.21 Operator detection system
- 12.22 Logging capabilities
- 12.23 Warning indication (mandatory warnings)
- 12.24 Test report

#### 13 Periodic verification

- 13.1 General
- 13.2 Testing requirements
- 13.3 Test object
- 13.4 Submission for testing
- 13.5 Preliminary inspection
- 13.6 Marking of the instrument and information in the instrument documentation

- 13.7 Test procedure
- 13.8 Test parameters
- 13.8.1 Vibration measurement chain for hand-arm vibration
- 13.8.2 Vibration measurement chain for whole-body vibration
- 13.8.3 Vibration measurement chain low-frequency whole-body vibration
- 13.9 Conducting the test
- 13.10 Test report
- 14 In-situ check
  - 14.1 General
  - 14.2 Preliminary inspection
  - 14.3 Vibration sensitivity (field calibration)

Annex A (informative) Treatment of transient acceleration artefacts

- A.1 Identifying and dealing with artefacts
- A.2 Principles of artefact treatment
- A.3 Treatment of artefacts
- A.3.1 General
- A.3.2 Cutting out the artefact
- A.3.3 Linearizing the artefact
- A.3.4 Substituting the artefact
- A.4 Example of hand-arm artefact treatment
- A.5 Example of whole-body artefact treatment

Annex B (informative) Influence of coupling force on hand-arm vibration evaluation

- B.1 General
- B.2 Measurement of coupling forces
- Annex C (informative) Human interface

Page count: 53